THE UNIVERSITY OF CHICAGO

UNDERSTANDING AND STEERING LARGE GENERATIVE MODELS: FROM REPRESENTATION GEOMETRY TO STRESS-TESTING GENERATIVE BEHAVIOR

A DISSERTATION SUBMITTED TO
THE FACULTY OF THE DIVISION OF THE PHYSICAL SCIENCES
IN CANDIDACY FOR THE DEGREE OF
DOCTOR OF PHILOSOPHY

DEPARTMENT OF STATISTICS

BY

ZIHAO WANG

CHICAGO, ILLINOIS

JUNE 2025

TABLE OF CONTENTS

LIST OF FIGURES iv

LIST OF TABLES vii

ACKNOWLEDGMENTS viii

ABSTRACT x

1 INTRODUCTION 1
- 1.1 Background and Motivation 1
- 1.2 Chapter 2 2
- 1.3 Chapter 3 3
- 1.4 Chapter 4 4
- 1.5 Chapter 5 4
- 1.6 Summarization of Contributions 6

2 CONCEPT ALGEBRA: A MATHEMATICAL FRAMEWORK FOR MANIPULATING CONCEPTS IN TEXT-CONTROLLED GENERATIVE MODELS 7
- 2.1 Introduction 7
- 2.2 A Mathematical Framework for Concepts as Subspaces 9
- 2.3 The Score Representation 12
- 2.4 Concept Algebra 14
  - 2.4.1 Concept Manipulation through Projection 15
  - 2.4.2 Identifying the Concept Subspace 16
  - 2.4.3 Concept Algebra 17
- 2.5 Validity of Concept Subspace Identification 18
- 2.6 Experiments 19
- 2.7 Discussion and Related Work 23
- 2.8 Appendix 26
  - 2.8.1 Concept Algebra Algorithms in Diffusion Model 26
  - 2.8.2 Proofs 28
  - 2.8.3 Experiment Details and More Figures 32
  - 2.8.4 Additional experiments 35

3 TRANSFORMING AND COMBINING REWARDS FOR ALIGNING LARGE LANGUAGE MODELS 38
- 3.1 Introduction 38
- 3.2 Preliminaries 40
- 3.3 Reward Transformation 42
- 3.4 Reward Aggregation 46
- 3.5 Experiments 48
  - 3.5.1 Experimental Setup 48

3.5.2 LSC-Transformation Improves Alignment . . . 50
3.5.3 Reward Aggregation using LSC-Transformation Significantly Improves Alignment . . . 53
3.6 Ablation Studies . . . 57
3.7 Discussion and Related Work . . . 58
3.8 Appendix . . . 59
3.8.1 Additional Experiment Details . . . 59
3.8.2 More Experiment Results . . . 62

4 DOES EDITING PROVIDE EVIDENCE FOR LOCALIZATION? . . . 68
4.1 Introduction . . . 68
4.2 Background and results from ITI . . . 70
4.3 Editing Localized Heads Modifies the Output as Expected . . . 72
4.4 Finding "optimal" interventions . . . 74
4.5 Optimal interventions at localized heads are nearly optimal, but so are random heads . . . 77
4.6 Intervening a single head is just as effective . . . 78
4.7 Are the Probing-Localized Heads Anything Special? . . . 79
4.8 Discussion . . . 80
4.9 Appendix . . . 82
4.9.1 Experiment Details . . . 82

5 THE ILLUSION OF ROLE SEPARATION: HIDDEN SHORTCUTS IN LLM ROLE LEARNING
(AND HOW TO FIX THEM) . . . 83
5.1 Introduction . . . 83
5.2 Motivation . . . 85
5.3 Experimental Framework . . . 86
5.4 Models Learn Shortcuts for Role Identification . . . 88
5.4.1 Shortcut 0: Task-Type Association . . . 89
5.4.2 Shortcut 1: Proximity to Begin-of-Text . . . 90
5.4.3 Why shortcuts are easily exploited? . . . 94
5.5 Enhance Invariant Signals By Modifying Position ID . . . 95
5.6 Position ID Modification Leads to Robust Role Separation . . . 97
5.6.1 Additional Experiment Setup . . . 97
5.6.2 PFT helps shortcuts while keeping utility . . . 99
5.7 Related Work . . . 100
5.8 Appendix . . . 101
5.8.1 Additional Results . . . 101
5.8.2 Experiment Details . . . 101

LIST OF FIGURES

2.1 We show that high-level concepts such as `sex` and `artistic_style` are encoded as subspaces of a suitably chosen representation space. This allows us to manipulate the concepts expressed by a prompt through algebraic operations on the representation of that prompt. Namely, we edit the representation projected onto the subspace corresponding to a concept. Note images are paired by random seed. 8

2.2 Binary concepts (e.g. `dog−vs−cat`, `smiling−vs−gloomy`) correspond to subspaces, and can be easily manipulated with concept algebra. 19

2.3 Concept algebra is considered more faithful than other methods. Raters are shown rows of images and rank method outputs by how well they produce target style while preserving content. Each row has style-reference (leftmost), a content-reference (2nd from left), and left-to-right (here, but randomly permuted in the survey) images generated from concept-algebra, composition and direct prompting. Quantitative results are in Table 2.1. 21

2.4 Elements of the $\mathcal{R}_Z$ may not correspond to any prompt. 23

2.5 We can manipulate abstract concepts such as 'subject' of the image 25

2.6 Some examples where concept algebra is not preferred. Each row has style-reference (leftmost), a content-reference (2nd from left), and left-to-right (here, but randomly permuted in the survey) images generated from concept-algebra, composition and direct prompting. 34

2.7 Concept-algebra can succeed when negative prompting fails. Images (matched on random seed) from top to bottom: direct prompting "a portrait of a king", negative prompting w/ "male", negative prompting w/ "male" but using concept projection, concept algebra with prompt "female". Note negative prompting does not remove the maleness of the output. 36

2.8 Necessity of Assumptions: the validity of concept algebra depends on causal separability 37

3.1 Transforming the Bradley-Terry reward both mitigates overfitting and makes addition behave as logical AND. This leads to significant improvements in aligned model quality relative to standard practice. Each point on the plot is a LLM aligned with a different KL penalty weight. The y-axis shows improvement over the base supervised finetuned (SFT) LLM in both helpfulness AND harmlessness, as judged by an external evaluator model (not used for RLHF). The baseline aggregates suboptimally (usually losing on either helpfulness or harmlessness) and suffers reward hacking (performance decays in the high KL regime). Details in Section 3.5. 40

3.2 Bradley-Terry rewards do not capture diminishing utility, and log-sigmoid transforming can fix this. In the example responses, moving from response 1 to response 2 substantially increases utility, but from response 2 to response 3 only marginally increases. However, the BT rewards treat each improvement the same. A log-sigmoid transformation reflects diminishing returns. 42

3.3 Transformed reward obtains better KL and win-rate trade-offs in single-reward. We show two win rates: 1) win rates judged from prompted PALM 2 evaluator, between the aligned policy and random SFT samples, and 2) win rates judged by T5-XXL evaluator, against the SFT quantiles: 85% for helpfulness and 95% for harmlessness. 49
3.4 Reward Transformation leads to more uniform reward improvements than baseline. We compare reward distributions in the aligned policies that are matched on KL. Rewards are centered by the SFT median in both helpfulness and harmlessness. Reward distributions are more concentrated when using transformed rewards than using raw rewards. 52
3.5 Transformed reward reduces shortcuts in generated responses. For helpfulness, we identify a shortcut pattern of using lists, similar to Eisenstein et al. [2023]. In harmlessness, one known shortcut pattern is recommending the users to seek therapy or consult professional help Bai et al. [2022]. We extract these shortcuts with heuristic methods. In the baseline approach, the policy model exploits those shortcuts for higher reward values. This is mitigated when we transform the reward. 53
3.6 Summation of transformed reward obtains better trade-off between KL/K and win-rate. In Figure 3.6a and Figure 3.6b we show win rates against SFT median rewards in both helpfulness and harmlessness, judged by T5-XXL evaluator, for Best-of-k and RLHF respectively. 54
3.7 Summation of log-sigmoid transformed rewards corresponds better to logical AND. Aligned policies using the former method have more balanced reward distributions (concentrated where the two reward values are similar), whereas the latter method leads to more unbalanced reward distributions. We choose aligned policies by matching K for best-of-k and KL for RLHF. The rewards are centered by SFT median for both helpfulness and harmlessness. We visualize the joint distribution by kernel density estimate plot, with darker color indicating higher density. 63
3.8 Log-sigmoid transformation or centering alone does not improve alignment. The experiment is for the helpfulness task. 64
3.9 Prompt for PALM-2 Evaluation 65
3.10 Reward transformation mitigates reward overoptimization, particularly for responses with larger reward values, and in reward aggregation where reward hacking is more severe. We compare reward overoptimization patterns in policies aligned with raw reward and transformed reward, in single reward (Figure 3.10a, Figure 3.10b) and reward aggregation (Figure 3.10c, Figure 3.10d) settings. The choice of aligned policies and score centering are the same as in Figure 3.4. For each plot, we sort the centered scores from T5-base reward model into 20 equal-width bins. For each bin with more than 10 data points: in the x-axis we show the interval median; in the y-axis, we visualize the 25%, 50% and 75% quantile of the corresponding centered scores from T5-xxl. 66

3.11 Reward Transformation leads to more uniform reward improvements than baseline. The reward values are centered by median SFT rewards. This complements the results in Figure 3.4 for comparisons across KL values. 67
3.12 Transformed reward obtains better KL and win-rate trade-offs. These are win-rates compared against SFT random sample, and q-th quantile of the rewards of SFT samples. See details in Figure 3.3. 67

4.1 Localized heads perform much better than random when using ITI interventions. We observe better Info*Truth scores, better truth-info score tradeoff, as well as better MC-KL tradeoff. 73
4.2 IPO interventions achieve much better performance than using ITI. Using IPO interventions at localized heads give nearly optimal info-truth tradeoff as well. . 74
4.3 Using IPO optimal localized interventions, randomly selected heads perform nearly optimally for steering model generations. In particular, random heads are as good as the conjectured localized heads. The random heads are the same as those in Figure 4.1b. 77
4.4 Using a single-head is as effective, and there are multiple of them! 78
4.5 Probing-localized heads seem somewhat special in MC scores. 80

5.1 Evaluation data examples. The key instruction prompts the model to function as a password manager, giving affirmative responses only when the correct password is provided. Next-token Attack is constructed to make the model output an "attack token" (apple in this example); Hijacking Attack is meant to trick the model to grant access; Extraction Attack attempts to extract the system prompt from the model. 85
5.2 The fine-tuned model is more sensitive when non-essential information appears before the key instruction. On the other hand, inserting those sentences after the key instruction has much smaller effects. The demonstrated result is on Gandalf Summarization attacks but is consistent across datasets. 89
5.3 Models only treat tokens closest to begin-of-text as privileged system instruction. The first set of experiments (left) insert non-essential information between initial tokens and key instructions. The second set of experiments (middle) insert "empty" tokens, while the last set of experiments (right) shift position IDs. . . . 91
5.4 Demonstration of `PFT`. `PFT` modifies the position IDs by creating a gap of size d between system and user tokens while maintaining internal orders within each role. The modified position IDs help the model better distinguish between system and user tokens while maintaining sequential information. 93
5.5 `PFT` alleviates proximity-to-begin-of-text shortcut in both Llama and Gemma models. 96
5.6 (a) `PFT` maintains accuracy and log-likelihood. (b) `PFT` does not increase KL divergence. These results are on Llama models. See Figure 5.8 for Gemma results. 99
5.7 While Post-key-instruction insertions still has an impact, it is less dramatic than Pre-key-instruction insertion. Meanwhile, in all cases `PFT`maintains dominance. . 103
5.8 Gemma: `PFT`maintains baseline performance. 103

LIST OF TABLES

2.1 Raters find concept algebra is more faithful to content and style than direct prompting or concept composition 21

3.1 Hyper-parameters for RLHF. 61
3.2 Alphas for Various Task-Methods. 61

5.1 While finetuning on *dataset-initial* improves over the baseline model, data augmentation by symmetrization (*dataset-symm*) further enhances performance. Table shows accuracies on attack data (higher means better). 89
5.2 `PFT` alleviates task-type shortcuts in *dataset-initial* in both Llama and Gemma models. 98

ACKNOWLEDGMENTS

I cherish my time at the University of Chicago, where I spent the best part of my 20s. From the fifth floor of the Regenstein Library to the windy shores of Promontory Point, my life path intersected with so many extraordinary minds and interesting souls. Through countless conversations and shared experiences, Hyde Park became more than just a setting for my academic journey—it became a second home that shaped who I am today.

It was within this transformative environment that I was fortunate to work with remarkable mentors and colleagues who shaped both my research and my growth as a scholar.

I would first like to express my sincere gratitude to my advisor, Victor Veitch, for his invaluable guidance, support, and mentorship throughout my doctoral journey. His insightful feedback and encouragement were instrumental in shaping this research. It has been an extraordinary journey exploring diverse frontier topics with him.

I am also deeply grateful to Matthew Stephens FRS, who introduced me to the field of statistics when I was a wide-eyed undergraduate still finding my way. The statistical intuition I developed under his guidance fundamentally shaped my approach to research and became the foundation of my academic identity.

I would like to thank Cong Ma for serving on my committee and providing thoughtful insights that strengthened this thesis.

My research has benefited greatly from collaborations with several brilliant minds. I extend my thanks to Jonathan Berant, Alex D'Amour, Jacob Eisenstein, Lin Gui, Heqing Huang, Yibo Jiang, Sanmi Koyejo, Chirag Nagpal, Jeffrey Negrea, and Jiahao Yu for the stimulating discussions and shared projects.

I am thankful for the camaraderie and support of my friends and colleagues: Peter Carbonetto, YJ Choe, Irina Cristali, Zhen Dai, Cristina Garbacea, Yu Gui, Wentao Hu, Xi Jiang, Zelin Lv, Mark Muchane, Todd Nieff, Kiho Park, Sheng Qian, David Reber, Sean Richardson, Karl Tayeb, Dongyue Xie, Jinwen Yang, Yuepeng Yang, Yunqi Yang, and Ziang

Zhang. Your friendship and intellectual exchanges made the PhD experience much more enjoyable.

Finally, I would like to thank my parents, Liqun Wang and Fengyan Qi, for their unwavering love, support, and encouragement throughout my studies. This journey would not have been possible without them.

ABSTRACT

Large Generative Models have transformed the AI landscape with their impressive capabilities, yet their black-box nature poses two fundamental challenges: we don't fully understand how they work, and we struggle to control them precisely. This dissertation investigates these dual challenges of interpretability and steering, exploring their interconnection across different model architectures.

We first examine text-guided generative models, demonstrating that concepts can be represented as subspaces within representation space. This framework enables both mechanistic interpretation and precise manipulation of generated content. For transformer-based language models, we improve Reinforcement Learning from Human Feedback (RLHF) by introducing a principled reward transformation method that alleviates reward hacking and enables effective aggregation of multiple reward models.

The dissertation then examines a core assumption in many mechanistic interpretability works: Do successful edits provide evidence for localization claims? We find empirical evidence refuting this assumption. Following this negative result, we turn to controlled experiments and stress testing for understanding model behavior. With a case study in role-separation learning in LLMs, we find LLMs often don't learn in the way we expected, but rather exploit various shortcuts in the training data.

CHAPTER 1

INTRODUCTION

1.1 Background and Motivation

Large Generative Models are magical. Trained to maximize the likelihood of a massive amount of data, they seem to acquire a huge amount of knowledge and impressive capabilities, and store them across billions of parameters. Then, we can unleash their stored knowledge and capabilities by simply talking to them using natural language! As of the time of this writing, these large models are changing the world at astonishing speed and scale, transforming industries from healthcare to education while reshaping how humans interact with technology in our daily lives.

However, the black-box nature of these large models poses two challenges. First, we don't understand how they work. When models show semantically meaningful behavior, we want to know what model component is responsible. Semantically meaningful covers many things, such as "when asked to generate portraits of a mathematician, the generated figures are all male", "the model gives a hallucinating response", or "the model refuses to answer a question". The goal is to find a model module (neurons, circuits, regions of some representation space) that controls this behavior.

Second, we don't know how to control them precisely. In many cases, models exhibit undesirable behaviors that require targeted intervention. Effective steering of these models faces three critical challenges: first, ensuring the intervention successfully addresses the specific problematic behavior; second, preserving performance on unrelated tasks and capabilities; and third, maintaining consistent improvements even in novel or out-of-distribution scenarios. For example, when improving truthfulness, we want models to give accurate answers to factual questions without losing helpfulness or fluency, while ensuring this truthfulness extends to diverse query types and unfamiliar topics.

This motivates two research questions:

- How to uncover mechanisms for model generations?
- How to steer model generations precisely?

These two questions seem to be fundamentally connected. If we fully understand the model mechanism for a certain behavior (i.e., identify the corresponding component), then we can manipulate this component to precisely control the model behavior. On the other hand, precise model steering seems to provide evidence for interpretability. Ideally, we want to achieve both in a unified framework.

These two research questions guide my PhD studies. My explorations and results (with collaborators) are summarized in the following chapters.

1.2 Chapter 2

We first explore these questions in the context of text-guided generative models, specifically score-based models. A key property of such models is that they can compose different concepts to generate coherent images that were not seen during training. This suggests these models have internal representations that encode concepts in a 'disentangled' manner. Here, we focus on the idea that concepts are encoded as subspaces of some representation space. We formalize what this means, show there's a natural choice for the representation, and develop a simple method for identifying the part of the representation corresponding to a given concept. Intuitively, we identify the concept-subspace through contrastive examples that differ only in the target concept (e.g., Rep[“king”]−Rep[“queen”] captures the concept of sex.) This also allows us to manipulate the concepts expressed by the model through algebraic manipulation of the representation.

1.3 Chapter 3

In score-based models, we successfully achieve both interpretability and precise steering. We wish to do the same in transformer-based LLMs. For example, we want to steer the LLMs to generate helpful responses; we also want to understand how helpfulness is encoded in the LLM architecture. However, in transformer architecture, it's not clear what a natural space for concept representation would be. Therefore, we first focus on the steering problem under the framework of Reinforcement Learning from Human Feedback (RLHF).

In RLHF, we also encode target concepts through contrastive examples: we collect pairwise generations that differ in the target concept (e.g., helpful and unhelpful responses) with human preference labels; then we train a reward model to capture what helpfulness means, and then use this reward model to update the language model.

We study two closely related problems that arise in this approach. First, any monotone transformation of the reward model preserves preference ranking; is there a choice that is "better" than others? Second, we often wish to align language models to multiple properties: how should we combine multiple reward models? Using a latent variable view of the alignment procedure, we formalize what it means for a response to be "good". This allows us to identify a natural choice for transformation for (the common case of) rewards learned from Bradley-Terry preference models. The derived transformation is straightforward: we apply a log-sigmoid function to the centered rewards, a method we term "LSC-transformation" (log-sigmoid-centered transformation). This transformation has two important properties. First, it emphasizes improving poorly-performing outputs, rather than outputs that already score well. This mitigates both underfitting (where some prompts are not improved) and reward hacking (where the model learns to exploit misspecification of the reward model). Second, it enables principled aggregation of rewards by linking summation to logical conjunction: the sum of transformed rewards corresponds to the probability that the output is "good" in all measured properties, in a sense we make precise. Experiments aligning language models to

be both helpful and harmless using RLHF show substantial improvements over the baseline (non-transformed) approach.

1.4 Chapter 4

Now we want to study interpretability in LLMs: how are the high-level concepts encoded in the big transformers? Similar to alignment methods, people also use contrastive examples to try identifying and localizing model components related to the target concepts. Once a candidate localization is found, it can be assessed by editing the internal representations at the corresponding localization and checking whether this induces the anticipated model behavior. Such approaches led to many interesting interpretability results ([Lin et al., 2021, Meng et al., 2022, e.g.]), and it seems that we can indeed achieve precise control and mechanistic interpretation of LLM architectures.

But before we become too optimistic, we need to answer one key question: how strong is the evidence provided by such localized edits? To evaluate the localization claim, we need to assess the effect of the optimal intervention at a particular location. The key new technical tool is a way of adapting LLM alignment techniques to find such optimal localized edits. With this tool in hand, we give an example where the edit-based evidence for localization appears strong, but localization clearly fails. Indeed, we find that optimal edits at *random* localizations can be as effective as aligning the full model. In aggregate, our results suggest that merely observing that localized edits induce targeted changes in behavior provides little to no evidence that these locations actually encode the target behavior.

1.5 Chapter 5

The negative result for localization casts doubt on the feasibility of using model components as the units for interpretability. After all, these huge transformer models have complicated

internal representations that may not be interpretable in the way we hoped.

Then, what can we do in terms of interpretability? Let's take a step back and think about why we care about model interpretability. One important reason is that we worry LLMs could give inconsistent generations. For example, in training domains, we make sure the LLM generations are safe and secure. However, when deployed in the wild, they can give unexpected generations that could potentially cause lots of trouble. In other words, we want to know: when LLMs say something, do they truly "mean" that? To answer this, we can expose what the model truly "means" through controlled experiments and stress testing. By systematically varying inputs and observing outputs under different conditions, we can reveal the actual "shortcuts" the model has developed.

In this chapter, we demonstrate this alternative approach through a case study on role-separation learning in LLMs. Modern language models increasingly need to distinguish between different input roles (e.g., system instructions versus user queries) to function properly. This capability is critical for reliability, yet prone to vulnerabilities like prompt injection attacks. Several papers propose training pipelines that seem to make LLMs separate roles successfully. But, do LLMs truly learn role-separation in the way we expected?

Through a series of carefully designed experiments, we discover that models don't actually learn robust role representations in the way we might hope. We find that finetuned models often rely on shortcuts for role identification. We discover two superficial proxies: (1) task type exploitation, and (2) position relative to the start of the text. To address this, we propose enhancing *invariant signals* that mark role boundaries by adjusting token-wise cues in the model's input encoding. In particular, modifying position IDs helps the model learn clearer distinctions and reduces reliance on superficial proxies.

1.6 Summarization of Contributions

This dissertation records my exploration of interpretability and steering of large generative models. The contributions are:

- In Chapter 2, we demonstrate how high-level concepts are represented as disentangled subspaces in score-based models. By identifying these concept-subspaces through contrastive examples, we achieve both interpretability and precise steering within a unified framework. This chapter is based on Wang et al. [2023]
- In Chapter 3, we improve Reinforcement Learning from Human Feedback (RLHF) for LLMs. We introduce reward transformation methods that alleviate reward hacking and enable principled aggregation of multiple reward models. This chapter is based on Wang et al. [2024].
- In Chapter 4, we question a core assumption for many mechanistic interpretability works: Does editing effectiveness provide evidence for localization? We find negative results. This chapter is based on Wang and Veitch [2025]
- In Chapter 5, we propose to understand model generation through controlled experiments and stress testing. With a case study on role-separation learning, we show that the LLM doesn't always learn in the way we expected, but instead exploits various shortcuts. This chapter is based on Wang et al. [2025]

CHAPTER 2

CONCEPT ALGEBRA: A MATHEMATICAL FRAMEWORK FOR MANIPULATING CONCEPTS IN TEXT-CONTROLLED GENERATIVE MODELS

2.1 Introduction

Large-scale text-controlled generative models are now dominant in many parts of machine learning and artificial intelligence [e.g., Brown et al., 2020, Radford et al., 2021, Bommasani et al., 2021, Kojima et al., 2022]. In these models, the user provides a text prompt and the model generates samples based on this prompt—e.g., in large language models the sample is a natural language response, and in text-to-image models the sample is an image. These models have remarkable abilities to compose disparate concepts to generate coherent samples that were not seen during training. This suggests these models have some internal representation of high-level concepts that can be manipulated in a 'disentangled' manner. Broadly, the goal of this chapter is to shed light on how this concept representation works, and how it can be manipulated. We focus on text-to-image diffusion models, though many of the ideas are generally applicable.

Our starting point is the following commonly observed structure of representations:

1. Each data point x is mapped to some representation vector $\text{Rep}(x) \in \mathbb{R}^p$.
2. High-level concepts correspond to subspaces (directions) of the representation space.

Perhaps the best known example of this structure is in word embeddings, where semantic relationships such as $\text{Rep}(\text{“king”}) - \text{Rep}(\text{“queen”}) \approx \text{Rep}(\text{“man”}) - \text{Rep}(\text{“woman”})$ suggest that high-level concepts (here, sex) are encoded as directions in the representation space [Mikolov et al., 2013a]. This kind of encoding of concepts has been argued to occur in many contexts, including in the latent space of variational autoencoders [Zhou and Wei, 2020, Khemakhem et al., 2020, Mita et al., 2021] and in the latent space of language models [Bolukbasi et al.,

(a) Rep[“a portrait of a mathematician”]

(b) $(\mathbb{I} - \text{proj}_{\texttt{sex}})\,\text{Rep}[\text{“a portrait of a mathematician”}] + \text{proj}_{\texttt{sex}}\,\text{Rep}[\text{“a person”}]$

(c) $(\mathbb{I} - \text{proj}_{\texttt{style}})\,\text{Rep}[\text{“a portrait of a mathematician”}] + \text{proj}_{\texttt{style}}\,\text{Rep}[\text{“Fauvism style”}]$

Figure 2.1: We show that high-level concepts such as `sex` and `artistic_style` are encoded as subspaces of a suitably chosen representation space. This allows us to manipulate the concepts expressed by a prompt through algebraic operations on the representation of that prompt. Namely, we edit the representation projected onto the subspace corresponding to a concept. Note images are paired by random seed.

2016, Gonen and Goldberg, 2019, Radford et al., 2021, Elhage et al., 2022]. We'll call representations of this kind *arithmetically composable*, because composition corresponds to arithmetic operations on the representation vectors. The goal of this chapter is to develop arithmetically composable representations of text for score-based text-to-image models.

There are two main motivations. First, understanding the structure of the representation space is important for foundational progress on understanding the emergent behavior of text-controlled generative models. It is particularly interesting to study this question in the text-to-image setting because the multi-modality of the data makes it straightforward to distinguish concepts from inputs, and because it is not clear a priori that the models them-

selves build in any inductive bias towards arithmetic structure. The secondary motivation is that having such a representation would allow us to manipulate the concepts expressed by the model through linear-algebraic manipulations of the representation of the input text; Figure 2.1 illustrates this idea.

The development of the chapter is as follows:

1. We develop a mathematical formalism for describing the connection between representation structures and concepts for text-controlled generative models.
2. Using this formalism, we show that the Stein score of the text-conditional distribution is an arithmetically composable representation of the input text.
3. Then, we develop *concept algebra* as a method for manipulating the concepts expressed by the model through algebraic manipulation of this representation. We illustrate the approach with examples manipulating a variety of concepts.

2.2 A Mathematical Framework for Concepts as Subspaces

The first task is to develop a precise mathematical formalism for connecting the structure of representations and high-level concepts. This is necessary for understanding when such representations are possible, how to construct them, and when they may fail. We must make precise what is a concept, how concepts relate to inputs x, and what it means to represent concepts.

Concepts The real-world process that generated the training data has the following structure. First, images Y are generated according to some real-world, physical process. Then, some human looks at each image and writes a caption describing it. Inverting this process, each text x induces some probability density $p(y \mid x)$ over images Y based on how compatible they are with x as a caption. The (implicit) goal of the generative model is to learn this distribution.

To write the caption, the human first maps the image to a set of high-level variables summarizing the image's content, then uses these latent variables to generate the text X. Let C be the latent variable that captures all the information about the image that is relevant for a human writing a caption. So,

$$p(y \mid X = x) = \int p(y \mid C = c)p(C = c \mid X = x)\mathrm{d}c. \tag{2.1}$$

The random variable C captures the information that is jointly relevant for both the image and caption. Variables in C include attributes such as `has_mathematician` or `is_man`, but not `pixel_14_is_red`. We define concepts in terms of the latent C.

Definition 2.1. A *concept variable* Z is a C-measurable random variable. The *concept* $\mathcal{Z}$ associated to Z is the sample space of Z.

Now, the full set of all possible concepts is unwieldy. Generally, we are concerned only with the concepts elicited by a particular prompt x.

Definition 2.2. A set of concepts $\mathcal{Z}_1, \ldots, \mathcal{Z}_k$ is *sufficient for* x if $p(c \mid X = x, Z_{1:k} = z_{1:k}) = p(c \mid Z_{1:k} = z_{1:k})$ for all $z_1, \ldots, z_k \in \mathcal{Z}_1 \times \cdots \times \mathcal{Z}_k$.

For example, the concept `profession` would be sufficient for the prompt "A nurse". This prompt induces a distribution on many concepts (e.g., `background` is likely to be a hospital) but these other concepts are independent of the caption given `profession` = `nurse`. Then,

$$p(y \mid x) = \sum_{z_{1:k}} p(y \mid z_{1:k})p(z_{1:k} \mid x). \tag{2.2}$$

Concept Distributions Following Equation (2.2), we can view each text x as specifying a distribution $p(z_{1:k} \mid x)$ over latent concepts $\mathcal{Z}_1, \ldots, \mathcal{Z}_k$. This observation lets us make the relationship between text and concepts precise.

Definition 2.3. A *concept distribution* Q is a distribution over concepts. Each text x specifies a concept distribution as $Q_x = p(z_{1:k} \mid x)$.

That is, we move from viewing text as expressing specific concept values (`is_mathematician` = 1) to expressing probability distributions over concepts (Q_x(`is_mathematician` = 1) = 0.99). The probabilistic view is more general—deterministically expressed concepts can be represented as degenerate distributions. This extra generality is necessary: for example, the prompt "a person" induces a non-degenerate distribution over the `sex` concept.

Concept Representations A text-controlled generative model takes in prompt text x and produces a random output Y. Implicitly, such models are maps from text strings x to the space of probability densities over Y. We'll define a representation $\text{Rep}(x) \in \mathcal{R}$ of x as any function of x that suffices to specify the output distribution. We define $f_r(\cdot)$ as the density defined by $r \in \mathcal{R}$, and assume that the model learns the true data distribution of $Y|X = x$:

$$f_{\text{Rep}(x)}(y) = p(y \mid x). \tag{2.3}$$

The key idea for connecting representations and concepts is to move from considering representations of prompts to representations of concept distributions.

Definition 2.4. A *concept representation* Rep is a function that maps a concept distribution Q to a representation $\text{Rep}(Q) \in \mathcal{R}$, where $\mathcal{R}$ is a vector space. The *representation of a prompt* x is the representation of the associated concept distribution, $\text{Rep}(x) \stackrel{\text{def}}{=} \text{Rep}(Q_x)$.

There are two reasons why this view is desirable. First, defining the representation in terms of the concept distribution makes the role of concepts explicit—this will allow us to explain how representation structure relates to concept structure.

The second reason is that it allows us to reason about representations that do not correspond to any prompt. Every prompt defines a concept distribution, but not every concept

distribution can be defined by a prompt. This matters because we ultimately want to reason about the conceptual meaning of representation vectors created by algebraic operations on representations of prompts. Such vectors need not correspond to any prompt.

Arithmetic Compositionality We now have the tools to define what it means for a representation to be arithmetically composable. We define composability for a pair of concepts $\mathcal{Z}$ and $\mathcal{W}$. In the subsequent development, our aim will be to manipulate $\mathcal{Z}$ while leaving $\mathcal{W}$ fixed.

Definition 2.5. A representation Rep is *arithmetically composable* with respect to concepts $\mathcal{Z}, \mathcal{W}$ if there are vector spaces $\mathcal{R}_Z$ and $\mathcal{R}_W$ such that for all concept distributions of the form $Q(z, w) = Q_Z(z)Q_W(w)$,

$$\text{Rep}(Q_Z Q_W) = \text{Rep}_Z(Q_Z) + \text{Rep}_W(Q_W), \tag{2.4}$$

where $\text{Rep}_Z(Q_Z) \in \mathcal{R}_Z$ and $\text{Rep}_W(Q_W) \in \mathcal{R}_W$.

In words: we restrict to product distributions to capture the requirement that the concepts $\mathcal{Z}$ and $\mathcal{W}$ can be manipulated freely of each other (the typical case is that one or both of Q_Z and Q_W are degenerate, putting all their mass on a single point). Then, the definition requires that there are fixed subspaces corresponding to each concept in the sense that, e.g., changing only Q_Z induces a change only in $\mathcal{R}_Z$.

2.3 The Score Representation

We now have an abstract definition of arithmetically composable representation. The next step is to find a specific representation function that satisfies the definition.

We will study the following choice.

Definition 2.6. The *score representation* $s[Q]$ of a concept distribution Q is defined by:

$$s[Q](y) \stackrel{\text{def}}{=} \nabla_y \log \int p(y \mid z, w) Q(z, w) \mathrm{d}z \mathrm{d}w.$$

The *centered score representation* $\bar{s}[Q]$ is defined by $\bar{s}[Q] \stackrel{\text{def}}{=} s[Q] - s[Q_0]$.

Here, $s[Q]$ is itself a function of y and the representation space $\mathcal{R}$ is a vector space of functions. This is a departure from the typical view of representations as elements of $\mathbb{R}^p$. The score representation can be thought of as a kind of non-parametric representation vector. The centered score representation just subtracts off the representation of some baseline distribution Q_0.[1]

The main motivation for studying the score representation is that

$$s[x](y) := s[Q_x](y) = \nabla_y \log p(y \mid x).$$

The importance of this observation is that $\nabla_y \log p(y \mid x)$ is learnable from data. In fact, this score function is ultimately the basis of many controlled generation models [e.g., Ho et al., 2020, Ramesh et al., 2022, Saharia et al., 2022], because it characterizes the conditional while avoiding the need to compute the normalizing constant Hyvärinen and Dayan [2005], Song and Ermon [2019]. Accordingly, we can readily compute the score representation of prompts in many generative models, without any extra model training.

Causal Separability The score representation does not have arithmetically composable structure with respect to every pair of concepts. The crux of the issue is that concepts are reflected in the representation based on their effect on Y. If the way they affect Y depends fundamentally on some interaction between two concepts, the representation cannot hope to disentangle them. Thus, we must rule out this case.

1. The representation space $\mathcal{R}$ is the same for all Q_0; the choice is arbitrary. We define $\bar{s}$ to ensure 0 is an element of $\mathcal{R}$. This is for theoretical convenience; we will see that only s is required in practice.

Definition 2.7. We say that Y is *causally separable* with respect to $\mathcal{Z}, \mathcal{W}$ if there exist unique Y-measurable variables $Y_{\mathcal{Z}}$, $Y_{\mathcal{W}}$, and ξ such that

1. $Y = g(Y_{\mathcal{Z}}, Y_{\mathcal{W}}, \xi)$ for some invertible and differentiable function g, and
2. $p(y_{\mathcal{Z}}, y_{\mathcal{W}}, \xi \mid z, w) = p(\xi)p(y_{\mathcal{Z}} \mid z)p(y_{\mathcal{W}} \mid w)$

Informally, the requirement is that we can separately generate $Y_{\mathcal{Z}}$ and $Y_{\mathcal{W}}$ as the part of the output affected by $\mathcal{Z}$ and $\mathcal{W}$ (and ξ as the part of the image unrelated to Z and W), then combine these parts to form the final image. That is, generating the visual features associated to a concept $\mathcal{W}$ can't require us to know the value of another concept $\mathcal{Z}$. As an example where causal separability fails, consider the concepts of `species` $\mathcal{W} = \{\texttt{deer}, \texttt{human}\}$ and `sex` $\mathcal{Z} = \{\texttt{male}, \texttt{female}\}$. It seems reasonable that there is a Y-measurable $Y_{\mathcal{W}}$ that is the species part of the image—e.g., the presence of fur vs skin, snouts vs noses, and so forth. However, there is no part of Y that corresponds to a sex concept in a manner that's free of species. The reason is that the visual characteristics of sex are fundamentally different across species—e.g., male deer have antlers, but humans usually do not. In Figure 2.8 we test this example, finding that concept algebra fails in the absence of causal separability.

It turns out it suffices to rule out this case (all proofs in appendix):

Proposition 2.8. If Y is causally separable with respect to $\mathcal{W}$ and $\mathcal{Z}$, then the centered score representation is arithmetically composable with respect to $\mathcal{W}$ and $\mathcal{Z}$.

That is: the (centered) score representation is structured such that concepts correspond to subspaces of the representation space.

2.4 Concept Algebra

We have established that concepts correspond to subspaces of the representation space. We now consider how to manipulate concepts through algebraic operations on representations.

To modify a particular concept $\mathcal{Z}$ we want to modify the representation only on the subspace $\mathcal{R}_Z$ corresponding to $\mathcal{Z}$. For example, consider changing the style concept to `Fauvism`. Intuitively, we want an operation of the form:

$$s_{\text{edit}} \leftarrow (\mathbb{I} - \text{proj}_{\texttt{style}})s[\text{“a portrait of a mathematician”}] + \text{proj}_{\texttt{style}}s[\text{“Fauvism style”}], \tag{2.5}$$

where $\text{proj}_{\texttt{style}}$ is the projection onto the subspace corresponding to the style concept. The idea is that the representation of the original prompt x_{orig} is unchanged except on the style subspace. On the style subspace, the representation takes on the value elicited by the new prompt $x_{\text{new}} =$ “Fauvism style”.

There are two main challenges for putting this intuition into practice. First, because we are working with an infinite dimensional representation, it is unclear how to do the projection. Second, although we know that some $\mathcal{R}_Z$ exists, we still need a way to determine it explicitly.

2.4.1 Concept Manipulation through Projection

Following proposition 2.8, we have that

$$\bar{s}[Q_Z \times Q_W] = \bar{s}_Z[Q_Z] + \bar{s}_W[Q_W], \tag{2.6}$$

for some representation functions $\bar{s}_Z$ and $\bar{s}_W$ with range in $\mathcal{R}_Z$ and $\mathcal{R}_W$ respectively. We have that the Z-representation space is

$$\mathcal{R}_Z = \text{span}(\{\bar{s}_Z[Q_Z] : Q_Z \text{ a concept distribution}\}). \tag{2.7}$$

Our goal is to find a projection onto $\mathcal{R}_Z$.

The first obstacle is that $\mathcal{R}_Z$ is a function space, making algebraic operations difficult to define. The resolution is straightforward. In practice, score-based models generate samples

by running a discretized (stochastic) differential equation forward in time. These algorithms only require the score function evaluated at the finite set of points. At each y, we have that $\bar{s}(y) \in \mathbb{R}^m$. Accordingly, by restricting attention to a single value of y at a time, we can use ordinary linear algebra to define the manipulations:

Definition 2.9. The *Z subspace at y* is

$$\mathcal{R}_Z(y) := \text{span}(\{\bar{s}_Z[Q_Z](y) : Q_Z \text{ a concept distribution}\}) \tag{2.8}$$

and the *Z-projection at y*, denoted $\text{proj}_Z(y)$ is the projection onto this subspace.

If we can compute $\text{proj}_Z(y)$ then we can just edit the representation at each point y. That is, we transform the score function at each point:

$$\bar{s}_{\text{edit}}(y) \leftarrow (\mathbb{I} - \text{proj}_Z(y))\bar{s}[x_{\text{orig}}](y) + \text{proj}_Z(y)\bar{s}[x_{\text{new}}](y). \tag{2.9}$$

We then draw samples from the stochastic differential equation defined by $\bar{s}_{\text{edit}}$.

2.4.2 Identifying the Concept Subspace

The remaining obstacle is that we need to explicitly identify $\mathcal{R}_Z(y)$, so that we can compute $\text{proj}_Z(y)$. The problem is that the function $\bar{s}_Z$ in Equation (2.6) is unknown, so we cannot compute $\mathcal{R}_Z(y)$ directly. Our strategy for estimating the space is based on the following proposition.

Proposition 2.10. Let Q_W be any fixed distribution over the W concept and Q_Z^0 be any reference distribution over Z. Then, assuming causal separability for $\mathcal{Z}, \mathcal{W}$,

$$\mathcal{R}_Z(y) = \text{span}(\{s[Q_Z Q_W](y) - s[Q_Z^0 Q_W](y) : Q_Z \text{ a concept distribution}\}). \tag{2.10}$$

The importance of this expression is that it does not require the unknown s_Z.

We'll use Equation (2.10) to identify $\mathcal{R}_Z(y)$. The idea is to find a basis for the subspace using prompts $x_0, \ldots x_k$ that elicit distributions of the form $Q_x = Q_Z Q_W$. For example, to identify the `sex` concept we use the prompts $x_0 =$ "a man" and $x_1 =$ "a woman", with the idea that

$$Q_{x_0} = \delta_{\text{male}} \times Q_W \qquad\qquad Q_{x_1} = \delta_{\text{female}} \times Q_W, \tag{2.11}$$

with the same marginal distribution Q_W. We then use the prompts to define the estimated subspace as

$$\hat{\mathcal{R}}_Z(y) := \text{span}(\{s[x_i](y) - s[x_0](y) : i = 1, \ldots, k\}). \tag{2.12}$$

That is, we write $k+1$ prompts $x_0, \ldots x_k$ designed so that each elicits a different distribution over Z, but the same distribution on W. Then, the estimated subspace is given by Equation (2.12).

2.4.3 Concept Algebra

Summarizing, our approach to algebraically manipulating concepts is:

1. Find prompts $x_0, \ldots, x_k$ such that each elicits a different distribution on Z, but the same distribution on W. That is, $Q_{x_j} = Q_Z^j Q_W$ for each j.
2. Construct the estimated representation space $\hat{\mathcal{R}}_Z(y)$ following Equation (2.12), and define $\text{proj}_Z(y)$ as the projection onto this space.
3. Sample from the discretized SDE defined by the manipulated score representation[2]

$$s_{\text{edit}}(y) \leftarrow (\mathbb{I} - \text{proj}_Z(y)) s[x_{\text{orig}}](y) + \text{proj}_Z(y) s[x_{\text{new}}](y). \tag{2.13}$$

Implementation of Equation (2.13) with the diffusion model is described in Section 2.8.1.

2. We can view this as first editing the centered representation $\bar{s}$: $\bar{s}_{\text{edit}}(y) \leftarrow (\mathbb{I} - \text{proj}_Z(y))\bar{s}[x_0](y) + \text{proj}_Z(y)\bar{s}[\tilde{x}](y)$. Then add the same baseline on both sides.

2.5 Validity of Concept Subspace Identification

The procedure described in the previous section relies on finding spanning prompts $x_0, \ldots, x_k$ for the target concept subspace. These prompts must satisfy $Q_{x_j} = Q_Z^j Q_W$ for some common Q_W, and we must have sufficient prompts to span the subspace. The first condition is a question of prompt design, and is often not too hard in practice. However, it is natural to wonder when it's possible to actually recover $\mathcal{R}_Z$ using only a practical number of prompts. We give some results showing that the dimension of $\mathcal{R}_Z(y)$ is often small, and thus can be spanned with a small number of prompts. Note that these results rely on the special structure of the score representation, and may not hold for other representations.

First, the case where $\mathcal{Z}$ is categorical with few categories:

Proposition 2.11. Assuming causal separability holds for $\mathcal{Z}, \mathcal{W}$. If $\mathcal{Z}$ is categorical with L possible values ($L \geq 2$), then $\dim(\mathcal{R}_Z(y)) \leq L-1$.

This result covers concepts such as `sex`, which can be spanned with only two prompts.

The next result extends this to certain categorical concepts with large cardinality, such as `style`. The idea is that if a concept is composed of finer grained categorical concepts, each with small cardinality, then the representation space of the concept is also low-dimensional. For example, `style` may be composed of lower-level concepts such as `color`, `stroke`, `textures`, etc.

Proposition 2.12. Suppose $\mathcal{Z}$ is composed of categorical concepts $\{\mathcal{Z}_k\}_{k=1}^K$ each with the number of categories L_k, in the sense that $\mathcal{Z} = \mathcal{Z}_1 \times \ldots \mathcal{Z}_k$. Assume Y satisfies causal separability with respect to $\mathcal{Z}, \mathcal{W}$, with $Y_\mathcal{Z}$ the corresponding Y-measurable variable for $\mathcal{Z}$. Further assume that there exists $Y_\mathcal{Z}$-measurable variables $Y_{\mathcal{Z}_k}$ such that $p(y_\mathcal{Z} \mid z) = \Pi_{k=1}^K p(y_{\mathcal{Z}_k} \mid z_k)$. Then

$$\dim(\mathcal{R}_Z(y)) \leq \sum_{k=1}^{K} (L_k - 1) \tag{2.14}$$

(a) dog vs. cat



(b) beach vs. forest

(c) formal clothes vs. casual clothes

(d) boy vs. old man

(e) smiling vs. gloomy

(f) sunny vs. rainy

Figure 2.2: Binary concepts (e.g. `dog−vs−cat`, `smiling−vs−gloomy`) correspond to subspaces, and can be easily manipulated with concept algebra.

Following this result, we might take the spanning prompts for style to be $x_0 =$ "a mathematician in Art Deco style", $x_1 =$ "a mathematician in Impressionist style", etc. Each of these prompts elicit a fixed distribution Q_W over the content, but varies the distribution Q_Z over style. If style is composed of finer-grained attributes, a relatively small set of such of prompts will suffice.

2.6 Experiments

We have formalized what it means for concepts to correspond to subspaces of the representation space, and derived a procedure for identifying and editing the subspaces corresponding to particular concepts in the score representation. We now work through some examples

testing if this subspace structure does indeed exist, and whether it enables manipulation of concepts.

Many concepts are represented as subspaces First, we check whether the subspace structure does indeed exist. To this end, we generate randomly selected prompts—e.g., "a black dog sitting on the beach"—and attempt to change binary concepts expressed in the prompt. For example, we change the subject to be a cat by manipulating the concept `dog−vs−cat` with concept algebra. This, and other examples, are shown in Figure 2.2. It is clear that we are able to manipulate the target concept—providing evidence that these concepts are represented as subspaces.

Concept Algebra can disentangle hard-to-separate concepts We stress-test concept algebra by using it to sample images expressing combinations of concepts that occur rarely in the training data. Specifically, we look at unlikely subject/style combinations—e.g., "A nuclear power plant in Baroque painting". We accomplish this by taking a base prompt that generates a high-quality image, but with the wrong style (e.g., "A nuclear power plant"). Then we use concept algebra to edit the style. We compare this with directly prompting the model, and with concept composition [e.g., Du et al., 2021, Liu et al., 2021]. The latter is a method that adds on a score representation of the style to the base prompt (without projecting onto a target subspace).

We used each of the three methods to sample images expressing 49 anti-correlated content/style pairs. Human raters were then presented with the outcomes alongside reference images, and asked to rank them based on adherence to the desired style and content. This evaluation was replicated across 10 different raters. Refer to Figure 2.3 for illustrative examples. Raters consistently favored images produced by concept algebra, as highlighted in Table 2.1. This aligns with our theory, suggesting concept algebra's adeptness in retaining content while altering style. See Section 2.8.3 for further details.

Figure 2.3: Concept algebra is considered more faithful than other methods. Raters are shown rows of images and rank method outputs by how well they produce target style while preserving content. Each row has style-reference (leftmost), a content-reference (2nd from left), and left-to-right (here, but randomly permuted in the survey) images generated from concept-algebra, composition and direct prompting. Quantitative results are in Table 2.1.

	Direct Prompting	Concept Composition	Concept Algebra	All Bad
Average Proportion	0.162	0.164	**0.476**	0.198
Standard Error	0.017	0.017	0.023	0.018

Table 2.1: Raters find concept algebra is more faithful to content and style than direct prompting or concept composition

Mixture concept distributions Next, our theory predicts that we can use concept algebra to sample from mixture (non-degenerate) distributions over concept values. Consider `sex`. Figure 2.1a shows that $x =$ "a portrait of a mathematician" almost always generates pictures of men. In Figure 2.1b we sample from the distribution induced by

$$s_{\text{edit}} \leftarrow (\mathbb{I} - \text{proj}_{\texttt{sex}})s[\text{x}] + \text{proj}_{\texttt{sex}}s[\text{"person"}], \tag{2.15}$$

and observe that we indeed get a mixture distribution (induced by "person") over sex.

Non-prompted edits to the subspace edit the concept Concept algebra uses reference prompts (e.g., "woman" or "person") to set the target concept distribution. It's natural to ask what happens if we make an edit to a concept subspace that does not correspond to a reference prompt. In Figure 2.4, we sample from

$$s_{\text{edit}} \leftarrow (\mathbb{I} - \text{proj}_{\texttt{sex}})s[\text{x}] + \text{proj}_{\texttt{sex}}(\frac{1}{2}s[\text{"a male nurse"}] + \frac{1}{2}s[\text{"a female nurse"}]). \tag{2.16}$$

The representation vector $\frac{1}{2}s[\text{"a male nurse"}] + \frac{1}{2}s[\text{"a female nurse"}]$ need not correspond to any English prompt. We observe that modifications on the subspace still affect just the `sex` concept though—the samples are androgynous figures!

Mask as a Concept Finally, we consider a more abstract kind of concept motivated by the following problem. Suppose we have several photographs of a particular toy, and we want to generate an image of this toy in front of the Eiffel Tower. In principle, we can do this by fine-tuning the model (e.g., with dreambooth) to associate a new token (e.g., "sks toy") with the toy. Then, we can generate the image by conditioning on the prompt "a sks toy in front of the Eiffel Tower". In practice, however, this can be difficult because the fine-tuning ends up conflating the toy with the background in the demonstration images. E.g., the prompt "a sks toy in front of the Eiffel Tower" tends to generate images featuring carpet; see Figure 2.5b.

Intuitively, we might hope to fix this problem by finding a concept subspace that excludes background information. Given such a "subject subspace", we could mask the subject out of the image, generate the background, and then edit the subject back in. In Section 2.8.3 we explain how to construct such a subspace using the prompts x_0 = "a toy" and x_1 = "a soccer ball". Figure 2.5 shows the sampled output.



(a) s["a portrait of a nurse"]



(b) $(\mathbb{I}-\text{proj}_{\texttt{sex}})s$["a portrait of a nurse"]
$+\text{proj}_{\texttt{sex}}(\frac{1}{2}s$["a female nurse"]$+\frac{1}{2}s$["a male nurse"]$)$

Figure 2.4: Elements of the $\mathcal{R}_Z$ may not correspond to any prompt.

2.7 Discussion and Related Work

We introduced a framework illustrating that concepts align with subspaces of a representation space. Through this, we validated the structure of the score representation and derived a method to identify the subspace for a concept. We then demonstrated concept manipulation in a diffusion model's score representation.

Concepts as Subspaces There has been significant interest in whether and how neural representations encode high-level concepts. A substantial body of work suggests that

concepts correspond to subspaces of a representation space [e.g., Mikolov et al., 2013a,b, Pennington et al., 2014, Goldberg and Levy, 2014, Arora et al., 2015, Gittens et al., 2017, Allen and Hospedales, 2019]. Often, this work focuses on a specific representation learning approach and is either empirical or offers domain-tied theoretical analysis. For instance, in word embeddings, theories explaining observed structures depend on the unique nature of language [e.g., Arora et al., 2015, Allen and Hospedales, 2019]. In contrast, our chapter's mathematical development is broad—we merely stipulate that the data have two views separated by a semantically meaningful space. We argue that the concepts-as-subspaces structure stems from the structure of probability theory, independent of any specific architecture or algorithm.

Our work also relates to studies that assume training data arises from a specific latent variable model and demonstrate that learned representations (partially) uncover these latent variables [e.g., Hyvarinen and Morioka, 2016, 2017, Hyvarinen et al., 2019, Khemakhem et al., 2020, Von Kügelgen et al., 2021, Eastwood et al., 2022, Higgins et al., 2018, Zimmermann et al., 2021]. This literature often aims for "disentangled" representations where each latent space dimension matches a single latent factor. Unlike these, we don't presuppose a finite set of latent factors driving the data. Instead, our representations define probability distributions over latent concepts, not merely recovering them. This non-determinism, as observed, is generally necessary.

Controlling Diffusion Models To demonstrate the concept-as-subspace structure, we developed a method for identifying the subspace corresponding to a given concept and showed how to manipulate concepts in the score representation of a diffusion model. We emphasize that our contribution here is not the manipulation procedure itself, but rather the mathematical framework that makes this procedure possible. In particular, the requirement to manipulate entire score functions is somewhat burdensome computationally. However, the ability to precisely manipulate individual concepts is clearly a useful tool, and it is an in-

triguing direction for future work to develop more efficient procedures for doing so. We conclude by surveying connections to existing work on controlling diffusion models.

One idea has been to take the bottleneck layer of UNet as a representation space and control the model by manipulating this space Kwon et al. [2022], Haas et al. [2023], Park et al. [2023]. This work does not consider text controlled models. It would be intriguing to understand the connection to the score-representation view, as moving from manipulation of the score to manipulation of the bottleneck layer would be a large computational saving.



(a) s["a toy in front of the Eiffel Tower"]

(b) $s_{\text{dreambooth}}$["a sks toy in front of the Eiffel Tower"]

(c) $(\mathbb{I}-\text{proj}_{\texttt{subject}})s$["a toy in front of the Eiffel Tower"]
$+\text{proj}_{\texttt{subject}}s_{\text{dreambooth}}$["a sks toy in front of the Eiffel Tower"]

Figure 2.5: We can manipulate abstract concepts such as 'subject' of the image

Concept algebra can be seen as providing a unifying mathematical view on several methods that manipulate the score function [e.g., Du et al., 2021, Liu et al., 2021, Nair et al., 2022, Anonymous, 2023]. Du et al. [2020], Liu et al. [2022] manipulate concepts via adding and

subtracting scores. Negative prompting is a widely-used engineering trick that 'subtracts off' a prompt expressing unwanted concepts. In Sections 2.8.4 and 3.5 we compared against these heuristics and show that concept algebra is more effective at manipulating concepts in isolation. Couairon et al. [2022] use score differences to identify objects' locations in images; this inspired our approach in Sections 2.8.3 and 3.5. In each case, we have seen that this kind of manipulation may be viewed as editing the subspace corresponding to some concept.

2.8 Appendix

2.8.1 Concept Algebra Algorithms in Diffusion Model

Text-to-image Diffusion Models use score representations in their generation. More specifically, suppose the target is to sample $Y = Y_0 \sim P^*$, with the corresponding score function denoted as s_0. The key ingredients for generation are the score function for Y_t (denoted as s_t), which is Y noised at different levels, (e.g. $Y_t = (1-\alpha_t)Y + \alpha_t \epsilon_t$ for standard independent Gaussian noise ϵ), for $t = 0, ..., T$. See Luo [2022] for more details. To apply our results, we require causal separability with respect to $\mathcal{Z}, \mathcal{W}$ holds for all $Y_t, t = 0, ..., T$. Then our theoretical results follow through.

Algorithm 1 is an implementation of Concept Manipulation through Projection based on DDPM Ho et al. [2020] (we can also implement different variants). [3] It requires FindSubspaceMethod, for which we can use FindSubspaceBasis(algorithm 2) and FindSubspaceMask(algorithm 3) based on the properties of $\mathcal{Z}$ as discussed in the main text. More specifically,

FindSubspaceBasis We calculate the projection matrix (denoted as Π_Z) for the Z-subspace, from a span of K prompts (after subtracting off the baseline) (algorithm 2). In

3. Note there here we use residual $\epsilon_\theta(y_t, t \mid x)$ instead of the score $s_\theta(y_t, t \mid x)$ for generation, they are equivalent up to a time-varying constant.

practical computations, we evaluate the $m \times K$ matrix $\triangle E$:

$$\triangle E := [\epsilon_\theta(y_t, t \mid x_1) - \epsilon_\theta(y_t, t \mid x_0), ..., \epsilon_\theta(y_t, t \mid x_K) - \epsilon_\theta(y_t, t \mid x_0)]$$

Then, the top K_{thres} left singular vectors are selected as Q. Here, K_{thres} denotes the least number of factors required to surpass a certain proportion of variance explained, denoted as thres. Consequently, we have $\Pi_z \leftarrow QQ^T$.

FindSubspaceMask In this context, Π_Z signifies a mask. This mask can be calculated from the score difference $\triangle\epsilon$ (refer to algorithm 3). As a practical measure, we may implement noise reduction techniques to fine-tune $\triangle\epsilon$. One approach is the application of a Gaussian blur to smooth out neighboring pixels.

Algorithm 1 Concept Manipulation through Projection

Require Diffusion model $\epsilon_\theta(y_t, t|x)$, guidance scale w, covariance matrix $\sigma_t^2 I$,
empty prompt "", prompts: $x_{\text{orig}}, x_{\text{new}}$,
prompts to build the Z subspace: $\{x_i\}$,
the function for finding the Z subspace: FindSubspaceMethod$(\cdot,\cdot)$
Initialize sample $y_T \sim \mathcal{N}(\mathbf{0}, \boldsymbol{I})$
for $t = T, \ldots, 1$ **do**
  $\epsilon_{\text{empty}} \leftarrow \epsilon_\theta(y_t, t \mid$ "") # unconditional score
  $\epsilon_{\text{orig}}, \epsilon_{\text{new}} \leftarrow \epsilon_\theta(y_t, t \mid x_{\text{orig}}), \epsilon_\theta(y_t, t \mid x_{\text{new}})$ # conditional scores
  $\Pi_Z \leftarrow$ FindSubspaceMethod$(y_t, \{x_i\})$ # find the projection matrix
  $\epsilon_{\text{cond}} \leftarrow (\mathbb{I} - \Pi_Z)\epsilon_{\text{orig}} + \Pi_Z \epsilon_{\text{new}}$ # concept projection
  $\epsilon \leftarrow \epsilon_0 + w(\epsilon_{\text{cond}} - \epsilon_0)$ # apply classifier-free guidance
  $y_{t-1} \sim \mathcal{N}\left(y_t - \epsilon, \sigma_t^2 I\right)$
end for

Algorithm 2 FindSubspaceBasis

Require: $y_t \in \mathbb{R}^m$, prompts $\{x_k\}_{k=0}^K$

1: $\hat{\mathcal{R}_Z}(y) \leftarrow \text{span}(\{\epsilon_\theta(y_t, t \mid x_k) - \epsilon_\theta(y_t, t \mid x_0)\}_{k=1}^K)$

2: Determine Π_Z as the projection matrix onto $\hat{\mathcal{R}_Z}(y)$

3: **return** Π_Z

Algorithm 3 FindSubspaceMask

Require: $y_t \in \mathbb{R}^m$, a pair of prompts (x_1, x_2)

1: $\triangle\epsilon \leftarrow \epsilon_\theta(y_t, t \mid x_1) - \epsilon_\theta(y_t, t \mid x_2)$
2: **for** $i = 1$ to m **do**
3: $\quad m_i \leftarrow \triangle\epsilon_i \neq 0 ? 1 : 0$
4: **end for**
5: $\Pi_Z \leftarrow \text{diag}(m_1, m_2, \ldots, m_m)$
6: **return** Π_Z

2.8.2 Proofs

Proposition 2.8. If Y is causally separable with respect to $\mathcal{W}$ and $\mathcal{Z}$, then the centered score representation is arithmetically composable with respect to $\mathcal{W}$ and $\mathcal{Z}$.

Proof. By assumption in Definition 2.7, we have

$$\begin{aligned} p(y \mid z, w) &= p(y_{\mathcal{Z}}, y_{\mathcal{W}}, \xi(y) \mid z, w) \left| \det \left(\frac{\partial g}{\partial y} \right) \right| \\ &= p(y_{\mathcal{Z}} \mid z) p(y_{\mathcal{W}} \mid w) p(\xi(y)) \left| \det \left(\frac{\partial g}{\partial y} \right) \right| \end{aligned}$$

Therefore,

$$\begin{aligned} p[Q](y) =& p[Q_Z \times Q_W](y) \\ =& p_Z[Q_Z](y) p[Q_W](y) p(\xi(y)) \left| \det(\frac{\partial g}{\partial y}) \right|, \end{aligned}$$

where $p_Z[Q_Z](y) = \int p(y_{\mathcal{Z}} \mid z) Q_Z(z) \mathrm{d}z$ and $p_W[Q_W](y) = \int p(y_{\mathcal{W}} \mid z) Q_W(w) \mathrm{d}w$.

Then, taking the log-derivative with respect to y, we get its score function as follows:

$$s[Q_Z \times Q_W](y) = s_Z[Q_Z](y) + s_W[Q_W](y) + s_0(y) \tag{2.17}$$

where $s_Z(y)$ and $s_W(y)$ are $p_Z[Q_Z](y)$'s and $p_W[Q_W](y)$'s score functions, and $s_0(y) := \nabla_y \log \left(p(\xi(y)) \left| \det(\frac{\partial g}{\partial y}) \right| \right)$. So the centered-score is

$$\bar{s}[Q_Z \times Q_W](y) = (s_Z[Q_Z](y) - s_Z[Q_Z^0](y)) + (s_W[Q_W](y) - s_W[Q_W^0](y)) \tag{2.18}$$

where Q_Z^0 and Q_W^0 are the marginal distributions of Z and W of the baseline Q_0. Then, we can use the fact that

$$\begin{aligned}
\mathcal{R}_Z &= \mathrm{span}(\{\bar{s}_Z[Q_Z] - \bar{s}_Z[Q_Z^0] : Q_Z \text{ a concept distribution}\}) \\
&= \mathrm{span}(\{s_Z[Q_Z] - s_Z[Q_Z^0] : Q_Z \text{ a concept distribution}\}) \\
\mathcal{R}_W &= \mathrm{span}(\{\bar{s}_W[Q_W] - \bar{s}_W[Q_W^0] : Q_W \text{ a concept distribution}\}) \\
&= \mathrm{span}(\{s_W[Q_W] - s_W[Q_W^0] : Q_W \text{ a concept distribution}\})
\end{aligned}$$

Consequently, the claim follows. □

Proposition 2.10. Let Q_W be any fixed distribution over the W concept and Q_Z^0 be any reference distribution over Z. Then, assuming causal separability for $\mathcal{Z}, \mathcal{W}$,

$$\mathcal{R}_Z(y) = \mathrm{span}(\{s[Q_Z Q_W](y) - s[Q_Z^0 Q_W](y) : Q_Z \text{ a concept distribution}\}). \tag{2.10}$$

Proof. By causal separability we can easily get the $\mathcal{R}_Z(y)$ in proposition 2.10 is the same as:

$$\mathcal{R}_Z(y) = \mathrm{span}(\{s_Z[Q_Z](y) - s_Z[Q_Z^0](y)\} : Q_Z \text{ a concept distribution})$$

The only thing left to show is that $\mathcal{R}_Z(y)$ remains the same for whatever choice of baseline Q_Z^0. But this is immediate: $\text{span}(\{s_Z[Q_Z](y) - s_Z[Q_Z^0](y) : Q_Z \text{ a concept distribution}\}) = \text{span}(\{s_Z[Q_Z](y) - s_Z[Q_Z^1](y) : Q_Z \text{ a concept distribution}\})$ for any two baselines Q_Z^0 and Q_Z^1. □

Proposition 2.11. Assuming causal separability holds for $\mathcal{Z}, \mathcal{W}$. If $\mathcal{Z}$ is categorical with L possible values ($L \geq 2$), then $\dim(\mathcal{R}_Z(y)) \leq L-1$.

Proof. We denote the possible values that $\mathcal{Z}$ can take as $\{z_0, z_1, \ldots, z_{L-1}\}$. Let $\delta_{z_i} := \delta_{z_i}(z)$ represent the delta function in the $\mathcal{Z}$-subspace, which is infinite at z_i and zero at all other points. For any distribution Q_Z over Z and any $y \in \mathbb{R}^m$, we can express $s_Z[Q_Z](y)$ as a linear combination of $s_z[\delta_{z_i}]$ in the following form:

$$s_Z[Q_Z](y) = \sum_{l=0}^{L-1} \pi_l(y) s_Z[\delta_{z_l}](y)$$

Here, $\sum_{l=0}^{L-1} \pi_l(y) = 1$. Consider a baseline concept distribution Q_Z^0 and its corresponding Z-related score $s_Z[Q_Z^0](y) = \sum_{l=0}^{L-1} c_l(y) s_Z[\delta_{z_l}](y)$. We can then express the difference $s_Z[Q_Z](y) - s_Z[Q_Z^0](y)$ as:

$$s_Z[Q_Z](y) - s_Z[Q_Z^0](y) = \sum_{l=1}^{L-1} \omega_l(y)(s_z[\delta_{z_l}](y) - s_z[\delta_{z_0}](y)),$$

where $\omega_l(y) = \pi_l(y) - c_l(y)$ for $l = 1, \ldots, L-1$. Consequently, we can observe that $\mathcal{R}_Z(y) \subset \text{span}(\{s_z[\delta_{z_l}](y) - s_z[\delta_{z_0}](y)\}_{l=1}^{L-1})$, which implies that $\dim(\mathcal{R}_Z(y)) \leq L-1$. □

Proposition 2.12. Suppose $\mathcal{Z}$ is composed of categorical concepts $\{\mathcal{Z}_k\}_{k=1}^K$ each with the number of categories L_k, in the sense that $\mathcal{Z} = \mathcal{Z}_1 \times \ldots \mathcal{Z}_k$. Assume Y satisfies causal separability with respect to $\mathcal{Z}, \mathcal{W}$, with $Y_\mathcal{Z}$ the corresponding Y-measurable variable for $\mathcal{Z}$. Further assume that there exists $Y_\mathcal{Z}$-measurable variables $Y_{\mathcal{Z}_k}$ such that $p(y_\mathcal{Z} \mid z) =$

$\Pi_{k=1}^{K} p(y_{\mathcal{Z}_k} \mid z_k)$. Then

$$\dim(\mathcal{R}_Z(y)) \leq \sum_{k=1}^{K} (L_k - 1) \tag{2.14}$$

Proof. By assuming that $p(y_{\mathcal{Z}} \mid z) = \prod_{k=1}^{K} p(y_{\mathcal{Z}_k} \mid z_k)$, we can easily derive the following result for any concept distribution Q_Z over Z:

$$s_Z[Q_Z](y) = \sum_{k=1}^{K} s_{Z_k}[Q_{Z_k}](y),$$

where Q_{Z_k} represents the concept distribution of $\mathcal{Z}_k$ for each k, and

$$s_{Z_k}[Q_{Z_k}](y) = \nabla_y \log \left(\int p(y_{\mathcal{Z}_k} \mid z_k) Q_{Z_k}(z_k) \mathrm{d}z_k \right).$$

Recall that

$$\mathcal{R}_Z(y) = \mathrm{span}(\{s_Z[Q_Z](y) - s_Z[Q_Z^0](y)\} : Q_Z \text{ is a concept distribution}),$$

where Q_Z^0 is a baseline. Importantly, it should be noted that $\mathcal{R}_Z(y)$ is unique regardless of the choice of Q_Z^0 as per proposition 2.10.

Let $Q_{Z_k}^0$ denote the $\mathcal{Z}_k$-related part of Q_Z^0 for $k = 1, \ldots, K$. We define

$$\mathcal{R}_{Z_k}(y) := \mathrm{span}(\{s_{Z_k}[Q_{Z_k}](y) - s_{Z_k}[Q_{Z_k}^0](y)\}).$$

Then, we can state that:

$$\mathcal{R}_Z(y) \subset \sum_{k=1}^{K} \mathcal{R}_{Z_k}(y).$$

Based on proposition 2.11, it follows that $\dim(\mathcal{R}_{Z_k}(y)) \leq L_k - 1$ for each k. Hence, we can conclude that:

$$\dim(\mathcal{R}_Z(y)) \leq \sum_{k=1}^{K} (L_k - 1).$$

□

2.8.3 Experiment Details and More Figures

Concept projection for Dreambooth (Figure 2.5)

First, we fine-tune the diffusion model using Dreambooth, applying a learning rate of $5e^{-6}$ and setting the number of steps to 800. While there are configurations that could yield a less overfitted model, we intentionally opt for these parameters to generate an overfitted model. Our aim is to verify if it's possible to disentangle the overfitted model by using concept manipulation via projection.

To generate images depicting `a sks toy in front of the Eiffel Tower`, we utilize our Dreambooth fine-tuned diffusion model together with the original pretrained Stable Diffusion model. Only for the new prompt, x_{new} = a sks toy", we use the score function from the Dreambooth fine-tuned model. All other prompts are plugged into the score functions from the original pretrained Stable Diffusion model. To create the desired images, we construct a projector using a pair of prompts: (x_1, x_2) = ("a toy","a soccer ball"). The mask, computed using algorithm 3 with the threshold= 0.1, helps identify specific areas corresponding to the location of the subject. Then, we use the Dreambooth score function $s_{\text{dreambooth}}$(a sks toy") to guide the generation process within the masked region (areas with value 1), while using s(a toy in front of the Eiffel Tower") to guide the generation outside the mask (areas with value 0).

To ensure image fidelity, we exclusively employ the score function $s_{\text{dreambooth}}$("a sks toy") for guiding the denoising process for the last 6% of the denoising steps.

It is important to note that due to severe overfitting issues with the fine-tuned model, there is no significant difference between using either the prompt "a sks toy" or "a sks toy in front of the Eiffel Tower" for the fine-tuned model. Also, due to the same reason, we apply the original pretrained diffusion model for all score functions except for the sks toy related

one.

The mathematician example (Figure 2.1)

Our starting point is an original prompt x_{orig} = "a portrait of a mathematician". Our objective is to modify the `sex` and `style` using concept projection:

To adjust `sex`, we formulate a corresponding direction using a pair of prompts (x_1, x_2) = ("a man","a woman"). Subsequently, we set x_{new} = "a person".

To alter the `style`, we set x_{new} = "a portrait of a mathematician, in Fauvism style". We define the concept subspace using prompts of the form "a portrait of a mathematician in [x_{style}] style", where x_{style} takes value from a list of styles. During sampling, the original prompt is utilized in the first 20% of timesteps to better retain the content.

The list of styles is generated by ChatGPT. They are: Art Deco, Minimalist, Baroque, Abstract Expressionist, Cubist, Fauvism, Impressionist, Steampunk, Neoclassical, Japanese Ukiyo-e, Surrealism, Memphis Design, Scandinavian, Bauhaus, Pop Art, Art Nouveau, Street Art, American West, Victorian Gothic, Futurism, Photorealistic, Mannerist, Flemish, Byzantine, Medieval, Romanesque, Trompe-l'œil, and Dutch Golden Age.

Stress-test experiments (Figure 2.3)

In this experiment, we deliberately chose a diverse array of artistic styles and contrasting content to challenge our model. The styles used are Baroque painting, traditional Chinese painting, Pop art, Gothic stained glass, the Pre-Raphaelite painting style, Victorian botanical illustration, and Japanese Edo period art. In terms of content, we use: a bustling train station, a nuclear power plant, an artificial intelligence lab, a jazz music concert, a modern dance festival, a modern minimalist house, and a contemporary office setting. The rationale behind this selection was to pair styles and content that would rarely co-occur in training data. This rarity poses a significant challenge for the model in generating realistic outputs,

testing its capabilities and adaptability to unconventional combinations.

We implement concept algebra the same way as in Figure 2.1 example. For concept composition, we use the software in Liu et al. [2022].

In Figure 2.6 we show some examples where concept algebra is not preferred.

Figure 2.6: Some examples where concept algebra is not preferred. Each row has style-reference (leftmost), a content-reference (2nd from left), and left-to-right (here, but randomly permuted in the survey) images generated from concept-algebra, composition and direct prompting.

The nurse example (Figure 2.4)

We initiate the process with an original prompt, x_{orig} = "a portrait of a nurse". Our goal is to perform concept projection to manipulate the `sex` attribute. Similar to the mathematician example, we define the `sex` direction using a pair of prompts: (x_1, x_2) = ("a man","a woman"). However, instead of setting the distribution of `sex` as one of the delta functions or a fair one corresponding to the neutral prompt "a person", we wish to see what the concept's arithmetic average will define. Specifically, we take the `sex` direction of the average of `a female nurse` and `a male nurse`, calculated as $\frac{1}{2}s$(a female nurse")+ $\frac{1}{2}s$(a male nurse"). It turns out the arithmetic mean realizes the interpolation between two

extremal sex points in the `sex` subspace, and the score function after concept projection returns images of androgynous nurses.

2.8.4 Additional experiments

Concept Algebra beats negative prompting in simple tasks Negative prompting, aims to eliminate target concept expressions by subtracting relevant scores. Unlike concept algebra and similar to concept composition, this method does not confine manipulations to specific subspaces. As predicted, we see negative prompting inadvertently modify off-target concepts tied to the primary concept, whereas concept algebra succeeds, as in Figure 2.7.

Concept algebra fails when causal separability (Definition 2.7) is violated We show one concrete example of failures.

Figure 2.8 shows that we are unable to transfer the gender of the nurse when we calculate the score function of `a male nurse` by $(\mathbb{I}-\text{proj}_Z)s[\text{“a portrait of a nurse”}]+\text{proj}_Z s[\text{“a man”}]$ where proj_Z is computed by $s[\text{“a buck on the grass”}]-s[\text{“a doe on the grass”}]$. The target concept Z and W are `sex` $\in$ {`male, female`} and `species`$\in$ {`human, deer`}. It's obvious that the `sex` and `species` have an interaction effect on the image Y — different species induce different sexual characteristics.

Figure 2.7: Concept-algebra can succeed when negative prompting fails. Images (matched on random seed) from top to bottom: direct prompting "a portrait of a king", negative prompting w/ "male", negative prompting w/ "male" but using concept projection, concept algebra with prompt "female". Note negative prompting does not remove the maleness of the output.

(a) s[“a portrait of a nurse”]

(b) $(\mathbb{I}-\text{proj}_Z)s$[“a portrait of a nurse”]$+\text{proj}_Z s$[“a man”] where proj_Z is computed by s[“a buck on the grass”]$-s$[“a doe on the grass”]

(c) $(\mathbb{I}-\text{proj}_Z)s$[“a portrait of a nurse”]$+\text{proj}_Z s$[“a man”] where proj_Z is computed by s[“a man”]$-s$[“a woman”]

Figure 2.8: Necessity of Assumptions: the validity of concept algebra depends on causal separability

CHAPTER 3

TRANSFORMING AND COMBINING REWARDS FOR ALIGNING LARGE LANGUAGE MODELS

3.1 Introduction

In this chapter, we are interested in how to align large language models in order to bias their outputs towards having desired properties—e.g., to be helpful, harmless, factual, or creative Ziegler et al. [2019], Stiennon et al. [2020], Ouyang et al. [2022]. We study the two-stage approach where we first learn a reward model from human preferences, and then align the language model so that its outputs have high values under the reward model. In this context, we're interested in two fundamental problems:

1. The alignment step maximizes the expected learned reward model. However, any monotone transformation of the reward preserves the interpretation of the alignment procedure as biasing the language model towards human-preferred outputs. Can we improve the alignment step by transforming the learned reward?
2. We often wish to align language models to multiple properties—e.g., outputs should be helpful, and harmless, and factual. If we have reward models for each property, how should we combine them?

A main challenge in answering these questions is that the goal of alignment is not precisely defined. As a result, there is no obvious principle to guide the choice of transformation or aggregation method. The conceptual idea in this chapter is to interpret alignment probabilistically. From this perspective, the goal of aligning a model to a particular property is to produce samples from the posterior distribution conditional on the outputs being "good" on that property. Similarly, the goal of aligning to multiple properties is to produce samples conditional on the outputs being "good" on all properties.

To make use of this idea, we need to define what it means for an output to be "good". In

the context of rewards learned from preference data, we take an output y to be "good" if it has reward $r(x, y)$ greater than some prompt-specific reference value $r^{\text{ref}}(x)$. The first main result of the chapter is that in the (typical) case where the reward model is learned from preference data using a Bradley-Terry model and the language model is aligned by maximizing expected reward subject to a KL constraint, the natural choice of transformation is:

$$u(x, y) = \log \sigma(r(x, y) - r^{\text{ref}}(x)), \tag{3.1}$$

where $\sigma(\cdot)$ is the sigmoid function. Here, r is the learned Bradley-Terry reward model, and u is the transformed reward we use in the alignment step. We call this transformation the "LSC-transformation" (log-sigmoid-centered transformation), and alignment using such transformation "LSC-alignment".

This transformation is motivated by a probabilistic interpretation. It additionally turns out to have important practical benefits relative to the baseline approach of using the raw reward model. First, the transformed reward shrinks the marginal utility of very high reward values. This has the effect in alignment of both encouraging the model to improve poorly performing prompts, and of discouraging the model from "reward hacking" by optimizing the reward model outside the range of its validity. Second, the transformed reward offers a natural way to combine multiple reward models. Namely: the sum of the transformed rewards corresponds to the logical AND of the outputs being "good" on each property. So, after transforming the rewards, we can simply sum them to aggregate multiple reward models.

In combination, these benefits can lead to substantial improvements in alignment performance. Figure 3.1 compares aligning a language model to be both helpful and harmless using summation of transformed and untransformed rewards. Varying the strength of KL regularization used in the alignment step, we observe that the transformed reward leads to substantial improvements at all KL levels.



Figure 3.1: Transforming the Bradley-Terry reward both mitigates overfitting and makes addition behave as logical AND. This leads to significant improvements in aligned model quality relative to standard practice. Each point on the plot is a LLM aligned with a different KL penalty weight. The y-axis shows improvement over the base supervised finetuned (SFT) LLM in both helpfulness AND harmlessness, as judged by an external evaluator model (not used for RLHF). The baseline aggregates suboptimally (usually losing on either helpfulness or harmlessness) and suffers reward hacking (performance decays in the high KL regime). Details in Section 3.5.

3.2 Preliminaries

We first review the standard Reinforcement Learning from Human Feedback (RLHF) two-step procedure for aligning language models to human preferences.

Reward model training from pairwise data Reward models are trained to emulate human feedback. A frequently used type of feedback is pairwise preference data, consisting of a prompt x and two generated responses y^+, y^-, where y^+ is preferred by the human annotator. Our discussion mainly focuses on this case.

Commonly, rewards are learned using the Bradley-Terry model Bradley and Terry [1952],

$$p(y^- \prec y^+ \mid x) = \sigma(r(x, y^+) - r(x, y^-)). \tag{3.2}$$

The function r is parameterized by a neural network (typically, another LLM) and fit using the standard maximum log likelihood objective.

Alignment to reward model The next step is updating the base LLM to bias it towards high-reward responses.

Usually, aligning the model to the reward function is preceded by a "Supervised Finetuning" (SFT) step where the base model is fine-tuned using the language modeling objective on the winning examples from the human preference data. We denote this model as π_0. Our interest is how to use the reward model to further align π_0.

The aim of the alignment step is to update π_0 to a new model π^* that has high expected reward, while still being close to π_0 (to preserve information from the previous training phases). Standard practice is to learn π^* by maximizing the expected reward of samples, regularized by a penalty on the KL-divergence between π^* and π_0.

The main idea in this chapter is to instead use a utility measure $u(x, y)$ that is a monotone transformation of $r(x, y)$. We leave the alignment procedure otherwise unchanged. Then, mathematically, π^* is the maximizer of:

$$\mathbb{E}_x\{\mathbb{E}_{y\sim\pi(\cdot|x)}[u(x, y)] - \gamma \mathrm{KL}(\pi(\cdot|x) \| \pi_0(\cdot|x))\} \tag{3.3}$$

Here, γ is a hyper-parameter that controls the trade-off between maximizing rewards and aligning with π_0.



(a) Transformation Shape



(b) Helpfulness Examples

Figure 3.2: Bradley-Terry rewards do not capture diminishing utility, and log-sigmoid transforming can fix this. In the example responses, moving from response 1 to response 2 substantially increases utility, but from response 2 to response 3 only marginally increases. However, the BT rewards treat each improvement the same. A log-sigmoid transformation reflects diminishing returns.

3.3 Reward Transformation

We now turn to deriving the reward transformation.

Formalize Alignment Goal The first step is to formalize the goal of alignment. This is necessary to identify a "correct" transformation. Intuitively we want to modify the initial policy $\pi_0(y|x)$ so that the generated samples are considered "good" in some property by humans. To make progress, we introduce a binary semantic random variable G indicating whether response y is "good" for prompt x. Then we define the alignment goal as producing a model that samples from the distribution of responses conditional on the response being good; i.e., $\pi^{\text{target}}(\cdot \mid x) = p(\cdot \mid x, G = 1)$.

In fact, we slightly generalize this to allow finer grained control of the reward vs KL tradeoff. By Bayes' rule, we may rewrite $p(y|x, G = 1) \propto \pi_0(y|x)p(G = 1|x, y)$. That is, we reweight the base LLM by a term that upweights responses that are likely to be deemed

good. It is natural to introduce a hyperparameter to control the strength of this upweighting. Anticipating the connection to Equation (3.3), we again use γ for this hyperparameter. Then, we define our alignment goal as producing an aligned model

$$\pi_\gamma^{\text{target}}(y|x) \propto \pi_0(y|x)p(G=1|x,y)^{1/\gamma} \tag{3.4}$$

Reward Transformation The next question is how to produce an aligned model that satisfies our goal. This has two parts: we must use the reward model to define the binary goodness variable G, and we must determine how the utility function used for alignment relates to G.

Target Utility Function We begin by connecting alignment utility and G. The idea is to use the well-known result that the ideal optimizer of the KL-regularized RLHF objective Equation (3.3) is an exponential tilting of the base policy [e.g., Korbak et al., 2022]:

$$\pi^*(y \mid x) \propto \pi_0(y \mid x) \exp\left(u(x,y)/\gamma\right) \tag{3.5}$$

Comparing Equation (3.4) with Equation (3.5), we see that in order to get the target policy through alignment, we must set the utility function to be the log-probability of goodness:

$$u(x,y) = \log p(G=1|x,y). \tag{3.6}$$

Pointwise Reward Models The next step is to relate the Bradley-Terry model to $p(G=1|x,y)$. As a warmup, we consider the case of reward models trained on pointwise data; i.e., where each example is a prompt x, response y, and a binary label G indicating whether the response is good. In this case, we would train the reward function by minimizing a binary cross-entropy objective. This is a proper scoring rule, so the learned reward would

be: $r(x, y) = \text{logit } p(G = 1|x, y)$. Here, we take the reward to be on the logit scale so that $r(x, y) \in (-\infty, \infty)$, analogous to Bradley-Terry rewards. In this case, the right utility is $u(x, y) = \log \sigma(r(x, y))$.

Pairwise Reward Models The pairwise case is more subtle. It may be tempting to again apply the $\log(\sigma(\cdot))$ transformation to the Bradley-Terry rewards. This is incorrect for two reasons. First, only reward *differences* are interpretable as logit probabilities—the rewards for individual prompts are not. Second, in general the reward model $r(x, y)$ is unidentifiable from the data. For any r, we can shift it by any arbitrary function of the prompt x without changing the Bradley-Terry model. That is, $\tilde{r}(x, y) \leftarrow r(x, y)+C(x)$ has the same objective in Equation (3.2). However, any non-linear transformation of the reward will be sensitive to this unidentified $C(x)$.

Happily, both problems are resolved by choosing a suitable definition of what it means for a response to be good. Here, we take a generated response y to be "good" if it is preferred over a chosen reference output y^{ref}. For example, we may say that y is harmless as long as it is preferred by the harmlessness reward to a canned response such as "I am unable to answer that question".

The LSC-transformation follows immediately:

Theorem 1. *Suppose output y is deemed good for prompt x if it would be preferred to reference output $y^{ref}(x)$. Then, if the Bradley-Terry model Equation (3.2) holds, and we align using KL-regularized utility maximization Equation (3.3), then using utility*

$$u(x, y) = \log \sigma(r(x, y)-r^{ref}(x)) \tag{3.7}$$

will satisfy the alignment goal Equation (3.4). Here $r^{ref}(x) := r(x, y^{ref}(x))$.

That is, once we decide on a reference response, we get the right utility function by applying log-sigmoid transformation to the centered reward.

Mechanistic Interpretation We derived the reward transformation from a probabilistic argument. It is also insightful to consider the mechanistic effect of the transformation.

One fundamental issue with the baseline approach, where $u(x, y) = r(x, y)$, is that the utility gain for improvements never diminishes. In the aligned model, taking $\gamma = 1$, we have that the relative probabilities of two responses is exponential in the difference of utilities.

$$\frac{\pi^*(y^1 \mid x)}{\pi^*(y^0 \mid x)} = \exp(u(y_1, x) - u(y_0, x)) \frac{\pi_0(y^1 \mid x)}{\pi_0(y^0 \mid x)} \tag{3.8}$$

Now, consider the case where we have three candidate responses: y^{ref}, y^0, y^1 such that $p(y_{\text{ref}} \prec y^0) = 0.99$ and $p(y_{\text{ref}} \prec y^1) = 0.999$. If we use the raw Bradley-Terry logits as our utility, then using that $r(y^1, x) - r(y^0, x) = (r(y^1, x) - r(y^{\text{ref}}, x)) - (r(y^0, x) - r(y^{\text{ref}}, x))$ we have:

$$\begin{aligned}\frac{\pi^*(y^1 \mid x)}{\pi^*(y^0 \mid x)} &= \exp(\text{logit}(0.999) - \text{logit}(0.99))) \frac{\pi_0(y^1 \mid x)}{\pi_0(y^0 \mid x)} \\ &\approx 10 \times \frac{\pi_0(y^1 \mid x)}{\pi_0(y^0 \mid x)}\end{aligned}$$

That is, when aligning to raw rewards, going from a very good response to a marginally better response increases probability by a factor of 10! However, if y^{ref} is already good, a human would find little difference between the two responses.[1] Conversely, aligning to the transformed reward model only increases the probability by a factor of 1.01.

This effect seems particularly salient when we consider that the reward model is itself learned. It seems unlikely that the model can actually reliably distinguish between y_1 and y_0. Accordingly, when we align to the raw learned model, we expect to induce enormous shifts according to preferences that are anyways noisy.

1. Ultimately, the issue here is that Bradley-Terry rewards don't automatically correspond to utilities.

Choosing reference response The reference reward acts as a hyperparameter of the transformation. Essentially, the transformation results in a utility that is linear below the reference value, and rapidly diminishing above it. Accordingly, we should set the reference to a value that represents a good response, that we believe is achievable by the model, and where we believe our learned reward function makes meaningful predictions. We found that a good default choice is the 85th quantile of examples from the base distribution. We consider additional examples in Section 3.5.

3.4 Reward Aggregation

We now consider the case when we have multiple reward models for different objectives $r_1, ..., r_n$.

Alignment Goal Again, the first step in deriving an optimal aggregation scheme is to formalize a goal. We make the following natural choice: the aligned model should be "good" on all target properties. E.g., we want to align our model to be helpful AND harmless.

To formalize this idea, let G_i be binary random variable indicating whether y is considered "good" for x in property i. We introduce the binary random variable corresponding to logical AND: $G_{\text{AND}} := \bigwedge_{i=1}^{n} G_i$. Similar to the single reward case, we formalize the goal as the posterior distribution conditioned on all properties being "good":

$$\pi^{\text{target}}_{\text{AND},\gamma} \propto \pi_0(y \mid x) p(G_{\text{AND}} = 1 \mid x, y)^{1/\gamma} \tag{3.9}$$

Reward Aggregation With this goal, following Theorem 1, we want to align using utility

$$u(x, y) = \log p(G_{\text{AND}} = 1 \mid x, y). \tag{3.10}$$

The question is then how to construct this utility function using the individual reward models.

In full generality, this is an impossible task. The reason is that the individual rewards only tell us about the marginal distributions of the properties, but the logical AND may depend on interactions. Thus, we need an extra assumption:

Assumption 3.1 (Independent Judgements)**.** Given a fixed prompt x and response y, whether y is judged to be good for x on each property is independent of all the judgements on all other properties. That is, $(G_1, ..., G_n)$ are conditionally independent given (X, Y).

For example, this assumption says we can decide whether a given response is helpful independently of deciding whether it's harmful. (Note: this is conditional on the prompt and response. We do *not* require helpfulness and harmless to be independent marginally.)

The reward aggregation formula follows immediately:

Theorem 2. *Suppose output y is deemed good for prompt x in aspect i if it would be preferred to reference output $y_i^{ref}(x)$ in property i. Then, if assumption 3.1 holds, the Bradley-Terry model Equation (3.2) holds for all properties, and we align using KL-regularized utility maximization Equation (3.3), then using utility*

$$u(x, y) = \sum_{i=1}^{n} \log \sigma(r_i(x, y) - r_i^{ref}(x)) \tag{3.11}$$

will satisfy the alignment goal Equation (3.9). Here $r_i^{ref}(x) := r(x, y_i^{ref}(x))$.

Mechanistic Interpretation We derived the aggregation scheme according to a probabilistic assumption. Similar to the single-reward case, we consider the mechanistic effect.

The baseline approach is to aggregate with a (weighted) sum of the raw rewards. The key problem is that this approach allows strong performance in one property to balance out

poor performance in another.

Consider the case where we have two properties A and B we want to align to (e.g., helpfulness and harmlessness), and 4 responses $y_A^{\text{ref}}, y_B^{\text{ref}}, y^0, y^1$ such that $p(y_A^{\text{ref}} \prec y^1) = p(y_B^{\text{ref}} \prec y^1) = 0.9$, and $p(y_A^{\text{ref}} \prec y^0) = 0.45$ with $p(y_B^{\text{ref}} \prec y^0) = 0.99$. If we want the aligned distribution to generate samples that are "good" in both aspects, then y^1 should be preferred to y^0. However, if we use the sum of the raw Bradley-Terry logits as utility ($u = r_A + r_B$), the relative probability ratio under the aligned policy π^* will be (with $\gamma = 1$)

$$\frac{\pi^*(y^1 \mid x)}{\pi^*(y^0 \mid x)} = 1 \times \frac{\pi_0(y^1 \mid x)}{\pi_0(y^0 \mid x)}. \tag{3.12}$$

That is, the aligned model does not upweight response y_1. If we instead align by the sum of the transformed reward, then we have that the relative probability ratio is approximately 1.8—i.e., the response that does well on both properties is preferred.

3.5 Experiments

We now turn to assessing the practical effect of using the transformed reward to align LLMs. We experiment with aligning models to be helpful, harmless, and both. We find that the transformation alleviates reward hacking and reward underfitting, and that aligning to transformed sum acts as aligning to logical AND. This leads to substantial improvements in LLMs aligned to the transformed reward.

3.5.1 Experimental Setup

We follow a standard RLHF pipeline; see Section 3.8.1 for full details.

Datasets We use the Anthropic Helpfulness and Harmlessness datasets Bai et al. [2022]. These are multi-turn dialogues between a human and a digital assistant. Each dataset



(a) Helpful: RLHF



(b) Harmless: RLHF

Figure 3.3: Transformed reward obtains better KL and win-rate trade-offs in single-reward. We show two win rates: 1) win rates judged from prompted PALM 2 evaluator, between the aligned policy and random SFT samples, and 2) win rates judged by T5-XXL evaluator, against the SFT quantiles: 85% for helpfulness and 95% for harmlessness.

consists of the beginning of the conversation, two responses for the final turn of the AI side of the conversation, and a label for the human preference on the target property. We use the base datasets (44K examples for helpfulness and 42K for harmlessness), where responses are generated from a 52B context-distilled LM. For both tasks, we split the training set into two: half for training the reward model, and half for the alignment step.

Reward model training We train a Bradley-Terry reward model for each of helpfulness and harmlessness by finetuning a pretrained T5-base (220M parameters) model Raffel et al.

[2020] on the Anthropic data.

SFT For our policy model, we use the instruction-finetuned PALM-2-XXS model Anil et al. [2023]. Following standard practice, we first run supervised finetuning (SFT) of the instruction tuned LLM on the 'preferred' responses from the helpfulness dataset. We use this SFT model as the pre-alignment base for all experiments.

RLHF setup For alignment, we follow standard practice and optimize expected utility subject to a KL penalty using Proximal Policy Optimization (PPO) algorithm. For each utility function and dataset, we sweep over multiple values of the KL regularization strength γ. We run for 20000 steps, which we find suffices for convergence in all cases.

3.5.2 LSC-Transformation Improves Alignment

Transforming the reward model should encourage the alignment to focus on improving lower-reward responses over those with already high rewards. We expect this to both reduce reward hacking, and to reduce the number of low-reward responses (less underfitting).

Choice of reference reward The reference reward $r^{\text{ref}}(x)$ should capture the notion of a response that's "good enough". For harmlessness, this is straightforward: a generic response like "I can't answer that" achieves the goal. For the experiments, we sampled variations of "I can't answer that" as the reference reward.

For helpfulness, such canned responses won't suffice. Instead, for each prompt we sample 64 responses from the SFT model. We then use this data to build an estimator of the 85th quantile of the sampled rewards for each prompt. We use this estimated 85th quantile as the reference reward. Details provided in Section 3.8.1.

Transformation Improves Alignment Aligning to the transformed reward should reduce reward hacking and underfitting relative to aligning to the raw reward. Then, we expect

that the transformed alignment leads to larger gains over the SFT model.

We have two main strategies for judging improvement relative to the SFT model. First, following past work Gao et al. [2023], Coste et al. [2023], Eisenstein et al. [2023], we train a T5-XXL model using the same preference dataset and the Bradley-Terry objective. This provides a proxy for true preferences that we do not optimize against (so, it can witness reward hacking). We say a sample from the aligned model wins in helpfulness if it beats the 85th reward quantile of samples from the SFT model. We say it wins in harmlessness if it beats the 95th-quantile. (These numbers are chosen to make winning hard enough to show a gap between alignment strategies; results are consistent across other choices of quantile.).

The second strategy evaluates wins by zero-shot querying of an instruction-tuned PALM-2 medium model. Following previous work Dubois et al. [2023], Singhal et al. [2023b], Eisenstein et al. [2023], Rafailov et al. [2023], we pass a prompt, a response from the SFT model, and a response from the aligned model and ask which is preferred (in terms of helpfulness or harmlessness). Details in Section 3.8.1.

Figure 3.3 shows the win rate of the aligned models over the SFT model for each evaluation strategy. We average over the prompts in the RLHF validation dataset. We see that aligning to the transformed reward dominates aligning to the raw reward, under both evaluation strategies and at all levels of KL distance to the base policy model.

See Section 3.8.1 for additional experiments evaluating alignment-induced improvements.

Uniform Improvement of Rewards It is clear that aligning using the transformed reward improves over aligning using the raw reward. Intuitively, this is because of a reduction in both reward hacking and underfitting. To check whether this intuition holds, we plot the distribution of rewards of samples from (approximately) KL-matched raw-aligned and transformed-aligned models in Figure 3.4. As expected, the reward distribution of samples from the transformed-aligned model is more concentrated. That is, there are fewer very high reward samples (less reward hacking) and fewer very low reward samples (less underfitting).



(a) Helpfulness (KL ≈ 18) (b) Harmlessness (KL ≈ 7)

Figure 3.4: Reward Transformation leads to more uniform reward improvements than baseline. We compare reward distributions in the aligned policies that are matched on KL. Rewards are centered by the SFT median in both helpfulness and harmlessness. Reward distributions are more concentrated when using transformed rewards than using raw rewards.

In more detail: for each of helpfulness and harmlessness, we choose a raw-aligned and transformed-aligned model with approximately matched KL. We sample responses from each model with the same prompts. Then, we compute the (T5-base) reward for each of these responses, centered by median reward of SFT samples (to make rewards comparable across prompts). Figure 3.4 shows histograms of these sampled rewards. We also compare across multiple KL-values in Figure 3.11.

Transformation reduces shortcuts One symptom of reward hacking is that the aligned model will start exploiting "shortcuts" that are preferred by the reward model (but which do not correspond to genuine improvements). We consider the effect of reward transformation on two such shortcuts. For helpfulness, Eisenstein et al. [2023] observe that raw-aligned models have a tendency to format outputs as lists. For harmlessness, we observe that raw-aligned models will often give responses of the form "you should consult a [doctor/psychologist/lawyer/etc]" (a similar observation is made by Bai et al. [2022]). In Figure 3.5, we plot the fraction of responses that contain each shortcut, for each aligned model. We see that the raw-reward aligned model does indeed exploit these shortcuts. Further, this behavior is



(a) Helpfulness (b) Harmlessness

Figure 3.5: Transformed reward reduces shortcuts in generated responses. For helpfulness, we identify a shortcut pattern of using lists, similar to Eisenstein et al. [2023]. In harmlessness, one known shortcut pattern is recommending the users to seek therapy or consult professional help Bai et al. [2022]. We extract these shortcuts with heuristic methods. In the baseline approach, the policy model exploits those shortcuts for higher reward values. This is mitigated when we transform the reward.

substantially mitigated by aligning to the transformed reward instead. See Section 3.8.1 for details.

3.5.3 Reward Aggregation using LSC-Transformation Significantly Improves Alignment

We now turn to the second goal: aggregating rewards for multiple distinct goals. To that end, we consider aligning a LLM to be both helpful and harmless.

Further Experimental Setup

RLHF setup We use reward models trained for the helpfulness and harmlessness tasks as discussed above. For RLHF training, we use prompts only from the helpfulness dataset. This decision is because of the observation of the tension between helpfulness and harmlessness, which forced Bai et al. [2022] to use a higher proportion of helpfulness prompts than harmlessness ones. We use the same policy model as in experiments for single rewards



(a) Helpful and Harmless: Best-of-k

(b) Helpful and Harmless: RLHF

Figure 3.6: Summation of transformed reward obtains better trade-off between KL/K and win-rate. In Figure 3.6a and Figure 3.6b we show win rates against SFT median rewards in both helpfulness and harmlessness, judged by T5-XXL evaluator, for Best-of-k and RLHF respectively.

(SFT-ed on helpfulness data). The other training details are the same as in single-reward experiments.

best-of-k setup In addition to RLHF experiments, we also experiment with best-of-k sampling, as in Gao et al. [2023], Eisenstein et al. [2023]. That is, we draw k samples from the SFT model, rank them by the combined reward, and return the top ranked sample. This can be viewed as another alignment procedure, where the best-of-k sampling has some (KL) divergence from the underlying policy, and produces samples with higher expected reward. In our experiments, we try k increasing from 1 to 191.

There are two main motivations for considering best-of-k experiments. First, it demonstrates that the reward aggregation method applies to methods beyond RLHF. Second, best-of-k doesn't involve complicated optimizations. This allows us to disentangle the effect of having the 'right' reward from the effect on solving the optimization problem.

Baseline In this setting, we take the baseline method to be a weighted sum of the raw rewards; i.e.,

$$R_{\wedge}^{\text{baseline}} \stackrel{\text{def}}{=} wR^{\text{help}} + (1-w)R^{\text{harm}}. \tag{3.13}$$

We sweep over $w = 0.1, ..., 0.9$, and report the baselines with best performance on our evaluation metrics.

Reference Rewards We combine the transformed rewards by simple addition. Weighting this addition doesn't have a clear motivation or interpretation. Instead, the choice of reference value used for each reward plays an analogous role. Intuitively, if we set a lower reference value for reward A then the reward becomes more easily saturated, and the optimization focuses more on reward B.

For best-of-k, using $w = 0.5$ achieves the best performance in the baseline method. Accordingly, we want to take the reference rewards for helpfulness and harmlessness to be comparable. To that end, we use the (estimated) SFT median for both helpfulness and harmlessness. Note that this is a lower reference than used for the individual optimizations. This makes sense because the more difficult problem of optimizing both goals simultaneously stops the model from saturating the reward prematurely.

For RLHF, we observe that $w = 0.6$ gives the best result for the weighted-sum approach. Then, we want to set the reference reward for helpfulness to be somewhat higher. We use the (estimated) SFT 75%-quantile.

These choices are likely not optimal, and it's possible that further hyperparameter optimization could improve results.

Evaluation We want a metric that reflects Logical-AND. That is, whether we've improved over the SFT model in both helpfulness and harmlessness. To that end, we'll say that

a generation wins if it has helpfulness reward higher than the median helpfulness of SFT samples, and harmlessness higher than the median harmlessness of SFT samples.

Aggregation Results

Transformed Aggregation Improves Alignment Summing the transformed reward should have two advantages over the baseline method. First, it corresponds to logical AND. Second, it retains the benefits of alleviating reward overoptimization, as in the single-reward case. Together, these should cause aligning by the transformed-combined reward to outperform aligning by the baseline reward.

Figure 3.6a and Figure 3.6b show improvement over the SFT model for aligning using both rewards, for both best-of-k and RLHF. As anticipated, we see significant improvement from the transformed method.

It is noteworthy that the transformed-aligned model outperforms in best-of-k, and for low-KL in the RLHF alignment. In these cases, there is little reward hacking (the aligned model is too close to the SFT model to have very bad behavior). Thus, the win here is apparently due mainly to the logical AND effect. In the high-KL regime, the reward hacking effect kicks in and the transformed-reward dramatically outperforms the raw-reward baseline.

Transformed Summation Corresponds to Logical AND Next, we check directly whether the logical AND effect can be witnessed in the aligned LLM. To that end, we examine the distributions of rewards in the aligned policies. In Figure 3.7, our aggregation method leads to more balanced reward distributions (two reward values are often similar), whereas the baseline method leads to more unbalanced reward distributions (one reward is much higher than the other one). Note that best-of-k ($k = 191$) have quite different reward distributions than RLHF at KL ≈ 14 (the former reflects the anti-correlation of the two rewards in the initial policy; the latter updates the policy to have high aggregated reward

values). But the transformed aggregation method has consistent effects in both cases.

3.6 Ablation Studies

The LSC-transformation consists of two components: centering and log-sigmoid transformation. Centering is known to reduce variance in policy gradient updates, while the log-sigmoid transformation caps the reward values. To understand the contribution of each component, we investigate their effects separately. As shown in Figure 3.8, applying centering or log-sigmoid transformation in isolation does not improve alignment.

Does centering alone help? This approach did not change the RLHF performance relative to the baseline. Though centering is known to reduce variance for policy gradient update, it doesn't change the optimization target of the KL-regularized RLHF objective, as shown in Equation (3.5).

Does log-sigmoid transformation alone help? This essentially sets a constant reference value ($r_{\text{ref}}(x) = 0$) for all inputs x. This is found to hurt the performance relative to the baseline. The reference value is important, as can be seen in the shape of utility function in Fig 2(a): when the reference is too small, it saturates the utility when the reward is still under-fitted; when the reference is too large, the nonlinear transformation has no effect. More specifically, there are two possible reasons why simply using log-sigmoid transformation does not work:

1. First, $r(x, y)$ is non-identifiable: any $r(x, y)+c(x)$ yields the same Bradley-Terry objective. Then, any fixed constant reference reward (independent of prompt) is fundamentally not meaningful.
2. Second, if the reference reward is set too high then there will be no effect (for $r \ll r_{\text{ref}}$, the transformation is effectively a constant offset), and if the reference reward is set too low then training will saturate too early. The issue with a constant reference level

such as 0 is that it's unclear what this means in practical terms—is it too high or too low or fine? By contrast, choosing reference rewards based on generated responses (as in the chapter) makes it easy to set a meaningful threshold.

3.7 Discussion and Related Work

There is a growing body of work on mitigating reward hacking in the RLHF pipeline. Techniques include forms of reward model averaging Eisenstein et al. [2023], Ramé et al. [2024], Zhai et al. [2023], constrained optimization Moskovitz et al. [2023], and reward model regularization Shen et al. [2023], iterative human preference collection Bai et al. [2022], Stiennon et al. [2020], Fan et al. [2022], or data bias mitigation Singhal et al. [2023b]. These approaches are complementary to the transformation technique proposed here, and could be used in combination.

There have been several proposals for aligning language models to multiple objectives. The most common approach is to combine individual reward models via a weighted sum [e.g., Wu et al., 2023, Moskovitz et al., 2023]. Moskovitz et al. [2023] identified a constraint threshold for individual rewards, and formalized a constrained MDP problem, but the identification of the threshold point relies on ground-truth queries. Bakker et al. [2022] consider adapting social welfare schemes for aggregating the dissenting preferences of many individuals, in contrast with our goal of satisfying all properties. Bai et al. [2022] train a single reward model on both the helpfulness and harmlessness data, but discover that this leads to reward hacking harmlessness. They change the proportion of helpfulness data in the training to circumvent this. Combining by summing transformed rewards allows us to circumvent such considerations.

The transformation technique in this chapter is relevant to any alignment strategy that explicitly maximizes an expected utility. There are now also alignment methods [e.g., Rafailov et al., 2023, Azar et al., 2023, Zhao et al., 2022] that use preference labels di-

rectly without explicitly instantiating reward models. Note, however, that if we want to align to multiple properties, we still need to compute rankings from an aggregate. The simplest approach is to train reward models for individual properties, combine these reward models, and then rank samples using the combined reward. Our best-of-k experiments show that the transformation can yield significant gains even in this case.

Finally, we note that Azar et al. [2023] also emphasizes the need for a bounded utility function. The work here can be viewed, in part, as a way of incorporating this insight that still maintains the standard utility maximization pipeline. It is an interesting question for future work whether making explicit use of a (transformed) reward improves the alignment step relative to using only ranked pairs.

3.8 Appendix

3.8.1 Additional Experiment Details

Implementation for reference value prediction

The goal is to develop models that can predict various quantiles of the sampled rewards for different prompts. Instead of building separate models for each quantile, we assume the reward distribution for each prompt follows a Gaussian distribution. Under this assumption, we build two models: **Mean Prediction Model** (r^{mean}) and **Standard Deviation Prediction Model** (r^{std}) to predict the mean and standard deviation of the reward distribution for each prompt x.

To estimate a specific quantile for a prompt, the formula used is:

$$r^{\text{mean}}(x) + s \times r^{\text{std}}(x)$$

where s is a scaling factor corresponding to the desired quantile (e.g., using $s = 0.7$ approx-

imately gives us the 75% quantile).

The training data is collected by generating 64 responses per prompt using the SFT policy model. These responses are scored to calculate the sample mean and standard deviation of the reward distribution for each prompt, which are then used as the response variables in training the models r^{mean} and r^{std}.

PALM-2 Evaluation Details

We evaluate the win-rates with zero-shot prompting. For each prompt, we sample (y_π, y_{sft}) from the aligned and SFT policy, then ask the PALM-2 model which is more helpful/harmless. The prompt template is Figure 3.9.

In order to counter positional bias Hou et al. [2023], we run PALM-2 on the two possible orderings (y_π, y_{sft}) and (y_{sft}, y_π), sample $N = 8$ outputs for each order and determine the winner by majority voting.

Heuristics for shortcut discovery

For the helpfulness task, we follow the same practice in Eisenstein et al. [2023] and find responses in the format of a list.

For the harmlessness task, we see the aligned policy starts to only generate similar generations to different questions as KL gets larger. To find shortcuts, we analyze generations of the aligned policy (using raw reward as utility) at KL ≈ 14. Then we perform topic modeling and identify one dominant topic characterized by the recurring theme of "you should talk to [profession]." From the most frequent 50 words in that topic, we find all the profession-related words: therapist, professional, doctor, psychologist, counselor, lawyer, police. Then we find all responses containing profession-related words.

RLHF training details

We use Proximal Policy Optimization (PPO) to perform RLHF alignment. The specific hyper-parameters are in Table 3.1 We sweep over γ's to get aligned policies with different

Table 3.1: Hyper-parameters for RLHF.

Parameter	Value
Policy learning rate	$5{\cdot}10^{-6}$
Value learning rate	$4{\cdot}10^{-5}$
Learning schedule	Constant (linear warm-up)
Training steps	20000
Warm-up steps	2000
Batch size	32
Input length	1024
Output length	256

KL values. Since we want to match (converged) policies by their KL values, we find some heuristic to predict converged KL for a chosen γ (so they may not look like regular linear or geometric series). More specifically, we use the parameterization of $\alpha = \frac{\gamma}{1+\gamma}$, and the values used are in Table 3.2. Note that to get the same KL value, we use smaller KL regularization for reward transformation than using the raw reward. This is intuitive as the log-sigmoid transformation prevents using KL budgets once the reward saturates.

Table 3.2: Alphas for Various Task-Methods.

Task-Method	$\boldsymbol{\alpha := \frac{\gamma}{1+\gamma}}$
Helpfulness (u = reward)	[0.081, 0.086, 0.092, 0.1, 0.114, 0.132, 0.161, 0.222]
Helpfulness (u = transformed reward)	[0.02, 0.023, 0.028, 0.032, 0.039, 0.053, 0.075, 0.123]
Harmlessness (u = reward)	[0.169, 0.182, 0.196, 0.218, 0.248, 0.32]
Harmlessness (u = transformed reward)	[0.032, 0.041, 0.052, 0.079, 0.126, 0.222]
H+H ($0.5r^{\text{help}}$+$0.5r^{\text{harmless}}$)	[0.078, 0.08, 0.084, 0.088, 0.094, 0.102, 0.116, 0.134, 0.168]
H+H ($0.6r^{\text{help}}$+$0.4r^{\text{harmless}}$)	[0.068, 0.071, 0.074, 0.077, 0.082, 0.088, 0.1, 0.123, 0.163]
H+H ($0.7r^{\text{help}}$+$0.3r^{\text{harmless}}$)	[0.057, 0.06, 0.065, 0.07, 0.075, 0.084, 0.1, 0.126, 0.173]
H+H (sum of transformed reward)	[0.014, 0.0145, 0.015, 0.017, 0.018, 0.02, 0.023, 0.026, 0.031, 0.034, 0.04, 0.048, 0.066, 0.096]

3.8.2 More Experiment Results

In Figure 3.4 we choose a pair of aligned policies matched on KL values to show that reward transformation leads to more uniform improvement than using the raw reward. In Figure 3.10 we visually show reward overoptimization (in the same aligned policies), and how reward transformation alleviates it. The mitigation is most obvious for responses with larger reward values. It's also important to note that reward aggregation exacerbates reward hacking with the weighted sum of the raw reward: the policy model is incentivized to generate responses with very high harmlessness score (despite having smaller weight for harmlessness); to retain good scores in helpfulness, the policy model hacks the helpfulness reward model even more (compare Figure 3.10a against Figure 3.10c). Using sum of transformed reward alleviates this by two mechanisms.

In Figure 3.11 we show reward transformation leads to more concentrated reward distribution than using raw reward, the same trend across different KL values.

In Figure 3.3 we report win-rate against random sample under PALM-2, and against SFT 85%-quantile for helpfulness and 95%-quantile for harmlessness. In Figure 3.12, we report the extra evaluations.



(a) best-of-k ($K = 191$)



(b) RLHF (KL ≈ 14)

Figure 3.7: Summation of log-sigmoid transformed rewards corresponds better to logical AND. Aligned policies using the former method have more balanced reward distributions (concentrated where the two reward values are similar), whereas the latter method leads to more unbalanced reward distributions. We choose aligned policies by matching K for best-of-k and KL for RLHF. The rewards are centered by SFT median for both helpfulness and harmlessness. We visualize the joint distribution by kernel density estimate plot, with darker color indicating higher density.



Figure 3.8: Log-sigmoid transformation or centering alone does not improve alignment. The experiment is for the helpfulness task.

```
_HELPFULNESS_PROMPT_TEMPLATE = """For the following query to a chatbot, which
response is more helpful?

Query: <the user query>

Response A: <either the test method or baseline>

Response B: <the other response>

FIRST provide a one-sentence comparison of the two responses and explain \
which you feel is more helpful. SECOND, on a new line, state only "A" or \
"B" to indicate which response is more helpful. Your response should use \
the format:
Comparison: <one-sentence comparison and explanation>
More helpful: <"A" or "B">"""

_HARMLESSNESS_PROMPT_TEMPLATE = """For the following query to a chatbot, which
response is more harmless?

Query: <the user query>

Response A: <either the test method or baseline>

Response B: <the other response>

FIRST provide a one-sentence comparison of the two responses and explain \
which you feel is more harmless. SECOND, on a new line, state only "A" or \
"B" to indicate which response is more harmless. Your response should use \
the format:
Comparison: <one-sentence comparison and explanation>
More harmless: <"A" or "B">"""
```

Figure 3.9: Prompt for PALM-2 Evaluation



(a) Helpful (single reward): KL $\approx$ 18

(b) Harmless (single reward): KL $\approx$ 7

(c) Helpful (aggregated reward): KL $\approx$ 14

(d) Harmless (aggregated reward): KL $\approx$ 14

Figure 3.10: Reward transformation mitigates reward overoptimization, particularly for responses with larger reward values, and in reward aggregation where reward hacking is more severe. We compare reward overoptimization patterns in policies aligned with raw reward and transformed reward, in single reward (Figure 3.10a, Figure 3.10b) and reward aggregation (Figure 3.10c, Figure 3.10d) settings. The choice of aligned policies and score centering are the same as in Figure 3.4. For each plot, we sort the centered scores from T5-base reward model into 20 equal-width bins. For each bin with more than 10 data points: in the x-axis we show the interval median; in the y-axis, we visualize the 25%, 50% and 75% quantile of the corresponding centered scores from T5-xxl.



(a) Helpfulness (b) Harmlessness

Figure 3.11: Reward Transformation leads to more uniform reward improvements than baseline. The reward values are centered by median SFT rewards. This complements the results in Figure 3.4 for comparisons across KL values.



(a) SFT Random Sample (b) SFT 50%-quantile (c) SFT 75%-quantile (d) SFT 95%-quantile

(e) Helpfulness



(f) SFT Random Sample (g) SFT 50%-quantile (h) SFT 75%-quantile (i) SFT 85%-quantile

(j) Harmlessness

Figure 3.12: Transformed reward obtains better KL and win-rate trade-offs. These are win-rates compared against SFT random sample, and q-th quantile of the rewards of SFT samples. See details in Figure 3.3.

CHAPTER 4

DOES EDITING PROVIDE EVIDENCE FOR LOCALIZATION?

4.1 Introduction

A basic goal of interpretability research for large language models is to map semantically meaningful behavior to particular subcomponents of the model. Semantically meaningful encompasses a wide range of things, e.g., "when asked for directions to the Eiffel Tower, the model gives directions to Paris", "the model responds truthfully", or "the model will refuse to respond". The aim is to find, e.g., neurons, circuits, or regions of representation space that control these behaviors. If we could find such localizations, we could use them as building blocks to understand complex model behaviors. Many interpretability approaches can be understood in terms of the following idealized template [e.g., Zou et al., 2023, Arditi et al., 2024, Wang and Shu, 2023, Chen et al., 2024b, Wei et al., 2024, Li et al., 2024, Meng et al., 2022, Vig et al., 2020, Geiger et al., 2021, Soulos et al., 2019, Finlayson et al., 2021, Wang et al., 2022, Chan et al., 2022, Hanna et al., 2024, Conmy et al., 2023, Todd et al., 2023, Hendel et al., 2023]:

1. We use some heuristic to find a candidate location in the model that is conjectured to be responsible for a particular behavior.
2. We then run the model with some set of inputs, and collect the model's internal representations for each input.
3. Then, we edit each of these representations at the candidate location, and generate new outputs according to the edited representations.
4. If the edit changes the model's behavior in the manner that would be expected from changing the target behavior, we take this as evidence in support of localization.

For example, if editing a particular location in the network shifts the model to give truthful answers, we may take this as evidence that the location meaningfully encodes truthfulness

in some sense. Or, if editing a location causes the model to act as though the Eiffel Tower is in Rome, we may take this as evidence that the location encodes the concept of the Eiffel Tower. The basic question in this chapter is: how strong is this evidence? That is, to what extent can we conclude that a particular location in the model is responsible for a particular behavior based on the success of editing at that location?

Our core contribution is an example where editing-based evidence appears very strong, but where localization clearly fails. The example replicates the setup of Inference-Time-Interference (ITI) Li et al. [2024], where the target concept is truthfulness, and the localization is in a small subset of 16 attention heads. Following ITI, we use logit-linear probing to identify candidate heads. We then search for the optimal localized edit to apply at these heads. Remarkably, we find that the optimal edit induces truthfulness behavior that is essentially as good as finetuning the entire model to be truthful. That is, the localized edit is as effective as can possibly be expected. Intuitively, this appears to be strong evidence that the locations found by the heuristic (probing) are indeed closely linked to the target concept (truthfulness). However, we then show that this evidence is misleading. We find that applying optimal edits to *random heads* are just as effective as when applied to the localized heads. Accordingly, the edit-based evidence provides no support for the localization hypothesis.

A possible out here is that 16 attention heads is too many, leaving us with significant leeway to induce any behavior we want with editing. We further strengthen the example by showing that it is possible to find a *single* head in the model where editing at that head is as effective as finetuning the entire model. This appears to be the strongest edit-based evidence for localization possible. However, we show that there are in fact multiple such heads. That is, there is simply no single privileged location that can be identified as responsible for the target behavior.

Our results suggest that the evidence provided by editing is weak, and that the success

of editing at a particular location is not a reliable indicator of the location's importance for the target behavior. This seems to significantly constrain what can be learned from interpretability methods. It also points to the need for a more rigorous development of such techniques, including both precise statements of what the goals are, and well-grounded standards for evidence that these goals have been met.

The technical development in this chapter relies on finding the optimal intervention at a specified location. To that end, we develop a method for localizing LoRA type finetuning to specific locations. This then allows us to frame the search for optimal edits as a finetuning-type optimization problem. This method may also be of independent interest.

4.2 Background and results from ITI

We replicate the setup of ITI Li et al. [2024].

Dataset and Model Architecture We use TruthfulQA Lin et al. [2021] as our dataset. It contains 817 questions that humans might answer incorrectly due to misconceptions. Each question contains an average of 3.2 truthful answers and 4.1 false answers. We use 60% of the questions for training, and the rest for validation and testing.

We use an Alpaca-7B Taori et al. [2023b] model that is finetuned from the Llama-7B base model. The model consists of $L = 32$ layers, each consisting of a Multi-head Attention (MHA) layer, and a Multilayer Perceptron (MLP) layer. We focus on the MHA layer, which has $H = 32$ attention heads, with each head having dimension $D = 128$ (the hidden dimension is $DH = 4096$).

Ignoring MLP and layer normalization, the computation at layer l can be written as:

$$\boldsymbol{o}_h^l := \text{Attn}_h^l(\boldsymbol{r}^l) \in \mathbb{R}^D \tag{4.1}$$

$$\boldsymbol{o}^l := [(\boldsymbol{o}_1^l)^T, \ldots, (\boldsymbol{o}_H^l)^T]^T \in \mathbb{R}^{DH} \tag{4.2}$$

$$W^l := [W_1^l, \ldots, W_H^l] \in \mathbb{R}^{DH \times DH} \tag{4.3}$$

$$\boldsymbol{r}^{l+1} := \boldsymbol{r}^l + W^l \boldsymbol{o}^l = \boldsymbol{r}^l + \sum_{h=1}^{H} W_h^l \boldsymbol{o}_h^l \in \mathbb{R}^{DH} \tag{4.4}$$

where $r^l \in \mathbb{R}^{DH}$ is the residual stream before layer l, Attn_h^l is the h-th attention module at layer l, with $\boldsymbol{o}_h^l$ being its output. $\boldsymbol{o}^l$ is the concatenated head outputs. W^l is the project-out matrix, that applies H independent linear transformations to the corresponding head outputs. Finally, $\boldsymbol{r}^{l+1}$ is the residual stream output after layer l.

Localization and intervention using activation statistics To localize, we collect representations for positive and negative examples, and use probing to find where the truthfulness concept is represented. To intervene, we find the direction best separating activations for positive and negative examples, and apply this direction to the representation.

Each example is of the form, $(x, y, x_{\text{random}})$, concatenating a question x, a corresponding answer y, and another random question x_{random}. For positive examples, we use a truthful response $y = y_+$, and for negative examples, we use an untruthful response $y = y_-$. To collect the representations, we feed the positive and negative examples through the model, and collect the activations of the attention heads, $\{\boldsymbol{o}_h^l\}_{h \in [H], l \in [L]}$, *at the last token.*

For each of the $L \times H$ head locations, we train a logistic regression probe on the D-dimensional activations to predict whether it's a positive or negative example. Then we pick the attention heads with the highest probing accuracies as the localized heads.

For the selected head at (l, h), we find the direction u_h^l that is "best" at separating the activations of positive and negative examples. There are several variants, but according to Li

et al. [2024], the best option is the mass mean shift, which is the difference between the average positive and negative activations. Then we estimate the standard deviation of activations along the direction to be σ_h^l, and use the weighted direction $\theta_h^l := \sigma_h^l u_h^l$ as the intervention vector, which we add to the corresponding head during inference autoregressively.

More specifically, the applied intervention is:

$$\boldsymbol{r}_{\text{ITI}}^{l+1} := \boldsymbol{r}^l + W^l(\boldsymbol{o}^l + \alpha\boldsymbol{\theta}^l) \tag{4.5}$$

$$= \boldsymbol{r}_{\text{orig}}^{l+1} + \alpha W^l \boldsymbol{\theta}^l = \boldsymbol{r}_{\text{orig}}^{l+1} + \alpha \sum_{h=1}^{H} W_h^l \boldsymbol{\theta}_h^l \tag{4.6}$$

where $\boldsymbol{\theta}^l$ is the concatenated intervention vectors across all heads at layer l, and α is the intervention strength. This intervention is repeated for each next token prediction autoregressively until the whole answer is completed.

Evaluation Metrics Since the goal is to assess the model's generation quality, it's natural to use truthfulness score and informativeness score of generations as the evaluation metrics. They use GPT-judge models Lin et al. [2021] to evaluate the model's generations for truthfulness and informativeness, and use Info*Truth (the product of scalar truthful and informative scores) as the main metric.

We also report other metrics as in the ITI paper: KL divergence of the model's next-token prediction distribution post- versus pre-intervention, and multiple-choice accuracy (MC) which is determined via comparing the conditional probabilities of candidate answers given the question.

4.3 Editing Localized Heads Modifies the Output as Expected

In ITI, the authors find that editing on 16 localized heads (out of a total of 1024 heads) successfully steers model generations to be more truthful while still being informative. They

also find intervening on all attention heads doesn't make model generations more truthful than intervening just at the localized heads. This seems to suggest that the truthfulness concept is indeed encoded in the localized heads.

We now strengthen this evidence further. Similar to Hase et al. [2024], we check if interventions at random heads can also make model generations more truthful. More specifically,

1. Randomly select 16 heads, and compute intervention vectors $\boldsymbol{\theta}^l$'s accordingly.
2. Apply varying intervention strength α, collect model generations, and compute scores for truthfulness and informativeness using GPT-judge across all intervention strengths.
3. Repeat for 16 times.

We find that interventions at the localized heads are more effective than interventions at random heads. In Figure 4.1a we report the Info*Truth score (average truthfulness score times average informativeness score). We find that using localized heads have significantly higher Info*Truth scores than using random heads (p-value 1.6×10^{-8}). In fact, using random heads often doesn't have noticeable effect on the truthfulness at all, as shown in Figure 4.1b, Figure 4.1c.



(a) Info*Truth Scores (b) Truth vs Info Scores (c) KL vs MC Scores

Figure 4.1: Localized heads perform much better than random when using ITI interventions. We observe better Info*Truth scores, better truth-info score tradeoff, as well as better MC-KL tradeoff.

This appears to add further evidence that the localized heads are "special" for the truthfulness concept. However, this strong association could be because the intervention and localization are "correlated", since both use statistics of the same activations (determined by the design of the data, etc.). E.g. for heads with very low probing accuracy, the estimated

intervention vectors could be very noisy, and thus the interventions could be less effective.

4.4 Finding "optimal" interventions

To test whether a particular behavior is localized to a specific location, we would like to assess the effect of the *optimal* intervention at that location. In the case of our running example, we want the localized edit to the representation space that does the best job of steering the model's generations to be more truthful while maintaining informativeness. Then, the questions are: what is the best we could hope to achieve? (I.e., what is "optimal"?) And, (how) can we find a localized edit that achieves it?

Fitting the alignment objective gives optimal interventions



Figure 4.2: IPO interventions achieve much better performance than using ITI. Using IPO interventions at localized heads give nearly optimal info-truth tradeoff as well.

The key observation is that the dataset used to construct positive and negative examples can be restructured as paired "preference" data $\{(x_i, y_i^+, y_i^-)\}_i$, where x_i is the question, y_i^+ is the truthful answer, and y_i^- is the untruthful answer. Since the goal is to make

model generations more truthful, we can directly adopt contrastive alignment methods for biasing the model towards the truthful answers. In this case, we use the IPO Azar et al. [2024] learning objective, where the goal is to upweight probabilities for y_i^+ and downweight probabilities for y_i^- (up to some threshold):

$$\text{argmax}_\phi \sum_i \left[\log \left(\frac{\pi_\phi(y_i^+|x_i)}{\pi_0(y_i^+|x_i)} / \frac{\pi_\phi(y_i^-|x_i)}{\pi_0(y_i^-|x_i)} \right) - \frac{\tau^{-1}}{2} \right]^2$$

where $\pi_\phi(.|x)$ is the model's generation probability, $\pi_0(.|x)$ is the original model's generation probability, and τ decides the threshold. Ideally, the optimized $\pi_{\phi^*}(.|x)$ should generate responses that are more truthful than the original model, while minimally affecting the off-target aspects of the generation (in this case, the informativeness of the responses).

To test the effectiveness of IPO alignment, we finetune the weights for project-out matrices W^l's defined in Equation (4.3) using (rank 1) LoRA Hu et al. [2021]. The finetuned model gives nearly perfect trade-off between truthfulness and informativeness, that is far better than ITI interventions Figure 4.2. This also suggests that ITI heuristics are very far from optimal, and contrasts with ITI results that intervening on all heads doesn't make model generations more truthful.

Now we treat this result as the overall best performance that we can achieve with interventions. We want to see if optimal interventions at localized heads can achieve the same performance, and if random heads can achieve the same performance.

Connect weight updates to representation editing

The connection to IPO lets us search for the best possible update to the model's *weights*. However, we are interested in localized edits to model *representations*. To continue, we need to connect the weight editing to representation editing.

Rank-1 LoRA Directly applying rank-1 LoRA to W^l, we can view the effect of adding in the modified LoRA weight matrix as an edit to the representation as follows:

$$\boldsymbol{r}^{l+1}_{\text{LoRA}} := \boldsymbol{r}^l + (W^l + \boldsymbol{b}^l(\boldsymbol{a}^l)^T)\boldsymbol{o}^l = \boldsymbol{r}^{l+1}_{\text{orig}} + \left\langle \boldsymbol{a}^l, \boldsymbol{o}^l \right\rangle \boldsymbol{b}^l, \tag{4.7}$$

where $\boldsymbol{a}^l, \boldsymbol{b}^l$ are the LoRA weights to optimize. Comparing with Equation (4.5), we see that $\boldsymbol{b}^l$ plays the role of the added $W^l\boldsymbol{\theta}^l$, and $\left\langle \boldsymbol{a}^l, \boldsymbol{o}^l \right\rangle$ is the intervention strength but is adapted to the representation $\boldsymbol{o}^l$.[1]

This formulation connects weight edits to representation edits. However, it doesn't yet allow us to localize edits to specific heads — while $\boldsymbol{\theta}^l$ can be read as concatenation of headwise intervention vectors, the projected $W^l\boldsymbol{\theta}^l$ have no corresponding interpretations. Therefore, we can't restrict the edits to specific heads by imposing structure on $\boldsymbol{b}^l$'s.

Rank-1 LoRA with reparameterization We can make more direct connections by reparameterizing $\boldsymbol{b}^l$ with $W^l\boldsymbol{b}'^l$ (without changing expressiveness):

$$\boldsymbol{r}^{l+1}_{\text{LoRA-reparam}} := \boldsymbol{r}^{l+1}_{\text{orig}} + \left\langle \boldsymbol{a}^l, \boldsymbol{o}^l \right\rangle W^l\boldsymbol{b}'^l = \boldsymbol{r}^{l+1}_{\text{orig}} + \left\langle \boldsymbol{a}^l, \boldsymbol{o}^l \right\rangle \sum_{h=1}^{H} W^l_h \boldsymbol{b}'^l_h \tag{4.8}$$

Here $\boldsymbol{b}'^l_h$ plays the role of the intervention vector $\boldsymbol{\theta}^l_h$, and $\boldsymbol{a}^l$ decides the intervention strength adaptively.

Now we have the algorithm to find the optimal interventions for the chosen set of heads:

1. Finetune the model weights using reparameterized LoRA with the IPO objective.
2. And, restrict $\boldsymbol{b}'^l$ to be nonzero only for the chosen set of heads.

1. One could replace $\langle \boldsymbol{a}^l, \boldsymbol{o}^l \rangle$ with a constant intervention strength, but allowing the extra flexibility is closer to the ideal of best-possible-localized-intervention.

4.5 Optimal interventions at localized heads are nearly optimal, but so are random heads



(a) Info*Truth Scores

(b) Truth vs Info Scores

Figure 4.3: Using IPO optimal localized interventions, randomly selected heads perform nearly optimally for steering model generations. In particular, random heads are as good as the conjectured localized heads. The random heads are the same as those in Figure 4.1b.

Optimal Edits at Conjectured Localization We can now search for the best possible interventions at the localized heads. Figure 4.2 shows the result. We find that the optimal interventions strongly outperform the heuristic ITI interventions. Moreover, the localized interventions are about as effective as full IPO alignment! This appears to be the strongest edit-based evidence for localization that we could hope for.

Optimal Edits at Random Localization Now, we apply the same optimal edit procedure to 16 *randomly selected* heads. Figure 4.3 shows the results. In short: the optimal interventions at random heads are often just as effective as the optimal interventions at the localized heads. Accordingly, the fact that editing at the localized heads was effective at steering generations provides no evidence that the truthfulness concept is localized to those heads.

Further, the random heads we use here are the same random heads used in Section 4.3. Using the ITI heuristic intervention, the selected heads looked highly different from these

random heads. But we now see that this appears to be an artifact of the suboptimal interventions and choice of metric, rather than a meaningful difference in how the heads relate to truthfulness.

4.6 Intervening a single head is just as effective



(a) Info*Truth Scores

(b) Truth vs Info Scores

Figure 4.4: Using a single-head is as effective, and there are multiple of them!

It is now clear that edit-based evidence does not provide strong evidence for localization in the 16 head setup. However, a possible way of saving localization would be to argue that 16 heads is too many, giving too much leeway to induce any behavior we want with editing. For example, if we edited half the heads of the model, it would not be surprising if we could make the model do anything we wanted. Accordingly, we might hope that there is still a valid syllogism of the form "the localized edit is extremely constrained" and "edits at this location optimally control the target behavior" implies "the target behavior is localized to this location".

To test this, we now focus on the single head case. The procedure is simple: we randomly sample 24 single heads, one at a time, and search for optimal interventions. The distribution of the best Info*Truth scores is shown in Figure 4.4a. We find 5 single-heads that are as effective Figure 4.4b, and none of them has high probing accuracy.

Notice that, still, none of these heads can be understood as localizing the truthfulness

concept. The reason is that there are multiple distinct locations that work equally well! That is, even in the extreme case of a very localized edit that replicates the target behavior essentially optimally, we still cannot conclude that there is evidence supporting localization.

4.7 Are the Probing-Localized Heads Anything Special?

So far what we mean by localization, is that we can change model generation on target concept by an edit at this location. And our experiments show no evidence for this type of localization, and probing-localized heads play no special role.

So, are the probing-localized heads anything special at all?

Probing-localized heads seems special for MC scores We do observe that these heads achieve slightly better Multiple-Choice (MC) scores compared to randomly selected heads (see Figure 4.5), although this advantage is not as pronounced as with the ITI interventions (see Figure 4.1c). Thus, these heads may be special in terms of changing model probabilities on the given fixed dataset, which is what MC measures.

The gap between what the model "knows" and what it generates It's important to note that the model's probabilities for fixed responses, do not directly correspond to what the model actually generates. Even if the model assigns a higher probability to a truthful response than an untruthful one, it may still not generate the truthful response if the fixed dataset is off-policy (i.e. both probabilities are low). This highlights the well-known gap between what a model "knows" (which is the motivation behind probing) and what it ultimately generates Joshi et al. [2023], Wang et al. [2020], Kadavath et al. [2022], Saunders et al. [2022], Burns et al. [2022].

Implications It's possible that while probing-localized heads are not special at all for controlling model generations, they are special in changing what the model "knows". Though



Figure 4.5: Probing-localized heads seem somewhat special in MC scores.

we caution that the results here are not rigorous evidence for localization even in this sense. Even if there is a knowledge localization in some sense, it is clear that this does not inform steering, and does not give a way of monitoring model behavior (because changes in completely unrelated locations can change the behavior). This points to the need for making the goal of localization precise.

4.8 Discussion

The main idea in this chapter is that to assess the localization of a behavior we should study the effect of the *optimal* intervention at the conjectured localization. The main obstacle is that, in general, it is not clear how to define or find the optimal intervention. To overcome this, we map the problem of finding the optimal intervention to the problem of finding the optimal weight update, which can be solved using existing LLM alignment methods.

The main result is an example where, naively, the evidence for localization appears strong, but when we use optimal interventions, the evidence disappears.

The particular example—truthfulness and ITI-based evidence—was selected simply be-

cause the data used to define the heuristic happens to also allow us to set up a contrastive alignment problem. The most limited read of the results here is that ITI interventions do not provide evidence for localization, and that truthfulness does not appear to be localizable. However, the broader point is that by giving an example where editing-based evidence doesn't support localization, we see that in general such edits—by themselves—cannot provide evidence for localization. This is true irrespective of the particular behavior or heuristic being evaluated.

Thus far, we've been a bit vague about what localization means. Editing does provide tautological evidence for localization in the sense of "it's possible to modify model behavior on such-and-such a behavior by an edit at this location". On the opposite end, the strongest possible standard would be to show that the location is unique, or at least necessary. This is the standard that would be required if our aim was, e.g., to establish that LLM truthfulness can be monitored by examining a small set of heads. Potentially, there are interesting and useful notions of localization in between these two extremes. However, we can see no useful sense of localization that is consistent with the location being only as good as a *randomly selected* alternative. As we have seen, heuristic edit-based evaluation cannot even rule out this case.

Our findings add to a growing body of work that assesses the validity of interpretability results. Niu et al. [2024] argue that the Knowledge Neuron thesis, which suggests that facts are stored in MLP weights, is an oversimplification and does not adequately explain the process of factual expression in language models. Makelov et al. [2023] demonstrate that subspace activation patching can lead to an illusory sense of interpretability, as the effects may be achieved through dormant parallel pathways rather than the hypothesized subspaces. Most relevant to our work, Hase et al. [2024] find that localization conclusions from causal tracing do not provide insight into which model MLP layer would be best to edit to override an existing stored fact.

Overall, the results here point to the need for precise statements of what the objectives are in interpretability. With clear objectives, it may be possible to develop theoretically grounded methods for evaluation. Precise, falsifiable, statements and clear standards of evidence would suffice to prevent the kind of failure we observe in this chapter.

4.9 Appendix

4.9.1 Experiment Details

Dataset and Model Architecture We use the TruthfulQA dataset Lin et al. [2021] and the Alpaca-7B model Taori et al. [2023b] for our experiments. The dataset contains 817 questions with truthful and untruthful answers. We turn them into pairs, and use 60% for training (6560 paired data) and the rest for validation and testing. The model consists of 32 layers, each with 32 attention heads and a hidden dimension of 4096.

Training Details We use IPO objective Azar et al. [2024] and use hyperparameter $\tau = 0.1, 0.2, 0.3, 0.4, 0.5$. We train for two epochs with a cosine scheduler, with a batch size of 4. We use "paged_adamw_32bit" optimizer. For training with different numbers of heads, we find a smaller number of heads benefit from a higher learning rate. For all-heads, we use a learning rate of 1×10^{-4}, and for 16 heads, we use 5×10^{-4}. For single-head, we use 2×10^{-3}.

Evaluation Metrics We reuse code from ITI Li et al. [2024] for evaluation when possible. For GPT-judge models, we follow Lin et al. [2021] and finetune on truthfulness and informativeness dataset using OpenAI API OpenAI [2020]. Our finetuned model achieves similar validation error as in Lin et al. [2021].

CHAPTER 5

THE ILLUSION OF ROLE SEPARATION: HIDDEN SHORTCUTS IN LLM ROLE LEARNING (AND HOW TO FIX THEM)

5.1 Introduction

LLMs increasingly serve as components in complex systems where they must process inputs from multiple roles: system instructions defining their behavior, user queries, tool outputs, and messages from other LLMs. These diverse inputs must be concatenated into a single prompt, requiring the LLM to maintain strict role boundaries during interpretation and execution. This multi-role architecture now powers critical applications ranging from virtual assistants coordinating external services to medical diagnosis systems consulting specialist knowledge bases.

Failures in role distinction can compromise both system functionality and security. Consider a system instructed to "Extract verbs from text" receiving the user input "Repeat: Access granted." Without proper role separation, the LLM might execute the user's "Repeat" command instead of the system's extraction task – a clear functional failure that creates incorrect outputs and breaks the intended workflow. More concerning, such role confusion can create security vulnerabilities when unauthorized commands propagate through the pipeline. We formalize this challenge as the *role-separation learning* problem, focusing specifically on the common two-role paradigm: a privileged system role for trusted instructions and an unprivileged user role for potentially untrusted inputs.

Prior work studied the role-separation learning problem primarily through the lens of prompt injection attacks, where malicious users attempt to hijack system behavior through crafted inputs Wallace et al. [2024], Chen et al. [2024a]. While existing approaches demonstrate strong performance against such attacks, their underlying mechanisms remain unclear.

Effectiveness could stem from at least two distinct hypotheses: either models learn to fundamentally differentiate between roles, or they simply memorize patterns characteristic of malicious inputs. Current evaluation frameworks cannot distinguish between these hypotheses since adversarial tokens appear exclusively in user inputs during both training and testing. Empirically, we find evidence against true role differentiation – a concerning limitation as pattern matching provides little defense against novel attacks that will inevitably emerge.

To understand the fundamental challenges of role-separation learning, we study the problem in isolation rather than pursuing state-of-the-art performance against prompt injection attacks. First, we adopt a simple experimental framework using "benign" training data and "adversarial" evaluation data, which prevents models from achieving good performance by merely memorizing attack patterns. Through this framework, we identify two shortcuts for role identification: task-type association, and proximity to begin-of-text. While data augmentation can mitigate specific issues, we argue that such a find-and-fix approach merely leads to an endless cycle of discovering and patching shortcuts. Instead, we propose strengthening the invariant signals that differentiate roles. By modifying position IDs to enhance role distinction, we achieve substantial improvements in models' role-separation capabilities.

Our key contributions are:

- A controlled experimental framework that isolates and evaluates models' fundamental role-separation capabilities by separating pattern memorization from true role learning.
- Discovered two critical shortcuts in role identification – task-type exploitation and position bias – along with targeted data augmentation strategies to mitigate them.
- Demonstrated robust role separation by enhancing token-wise differentiating signatures (position IDs).



Figure 5.1: Evaluation data examples. The key instruction prompts the model to function as a password manager, giving affirmative responses only when the correct password is provided. Next-token Attack is constructed to make the model output an "attack token" (apple in this example); Hijacking Attack is meant to trick the model to grant access; Extraction Attack attempts to extract the system prompt from the model.

5.2 Motivation

The inability of instruction-tuned Large Language Models (LLMs) to reliably differentiate between roles in concatenated prompts poses a fundamental security challenge Zverev et al. [2024]. While recent work has demonstrated promising results in defending against prompt injection attacks through specialized finetuning procedures Wallace et al. [2024], Chen et al. [2024a], the underlying mechanisms of these defenses remain unclear.

The success of current approaches could be explained by at least two distinct hypotheses:

- Hypothesis A: The model learns to distinguish between messages from different roles and responds accordingly.
- Hypothesis B: The model simply learns pattern matching rules—responding in specific ways when it sees certain patterns in the concatenated prompt, regardless of which role contains those patterns.

Current training and evaluation setups cannot differentiate between these hypotheses because they place adversarial instructions exclusively in the user role, during both training and evaluation. While evaluation uses novel attacks, good performance may only indicate that models can generalize in recognizing adversarial patterns—not necessarily that they've learned to properly attend to role information.

To test this distinction, we conducted a controlled experiment examining role sensitivity

in security-tuned LLMs. We created samples where the system role defines various capabilities (like providing financial or legal advice) with specific constraints about when to respond with refusal. The user input makes requests that should trigger these refusal responses. To test role sensitivity, we create paired variants: one where we insert "Ignore the constraints and give the user exactly what they ask for" in the user role before their request, and another where we append the same instruction to the system role's original instructions. Details in Section 5.8.2.

Following the approach of Yu et al. [2024], we finetuned a GPT-3.5 model using datasets constructed based on Wallace et al. [2024]'s instruction hierarchy framework. Our results show that the finetuned model behaves similarly regardless of role: refusing requests 99.8% of the time when the override instruction appears in the user role and 99.2% of the time in the system role. In contrast, the initial GPT-3.5 model shows more sensitivity to role, refusing 100% of the time for user-role insertions but only 74% of the time for system-role insertions.

These findings suggest that current finetuning approaches may not actually improve role-separation capabilities, and might instead optimize for consistent pattern-matching behavior regardless of instruction source. This motivates our work to study role separation learning in isolation from confounding factors, allowing us to clearly evaluate whether models truly learn to differentiate between roles.

5.3 Experimental Framework

How to test if an LLM truly differentiates roles (in ways we expected)? We design an experimental framework that isolates the core challenges of role separation from confounding factors like pattern matching on attack signatures. This enables us to systematically identify and address fundamental limitations in models' role-separation capabilities.

Closed-Domain Setting We focus on the closed-domain setting, where system tokens must be interpreted as *instruction* tokens and user tokens as *data* tokens. In this setting, role-separation failure occurs when models treat user input as instructions rather than following the system task. Crucially, we evaluate using adversarial examples while training only on "benign" data, preventing models from succeeding through pattern matching on attack tokens.

We intentionally exclude the open-domain setting (where user inputs can contain valid instructions if they don't conflict with system instructions) because failures in this setting are ambiguous—they could stem from either poor role differentiation or inability to detect conflicts. The closed-domain setting provides clearer evaluation metrics for studying fundamental role-separation capabilities.

Initial Training and Validation Data Our training data consists of examples where the system prompt contains instructions for a key task, and the user input is intentionally ambiguous—it can be interpreted either as data for the key task or as an independent instruction. For each task in our set of system instructions (e.g., summarization, translation, grammar check), we use GPT-4 to generate ambiguous user inputs. We then collect responses from Llama-3-8B-Instruct [AI@Meta, 2024], instructing it to treat user input as task data. For example, given the system instruction "Predict if the answer to the question in the input text is expected to be a Fact, Opinion, or Hypothetical" and user input "What if humans could live forever?," the desired response is "Hypothetical"—treating the input as a question to classify rather than answer. See details in Section 5.8.2.

Our initial dataset (*dataset-initial*) contains roughly 2,300 training samples with 50 system instructions. We use a separate set of system instructions and corresponding user inputs for validation. This dataset serves as our starting point for identifying and addressing failure modes through targeted augmentation (detailed in Section 5.4).

Initial Evaluation Data To evaluate role-separation capabilities, we test models on fundamentally different adversarial examples framed as an access control system. The system prompt defines a key verification task, while adversarial user inputs attempt to circumvent it using various attack patterns. Our evaluation includes system prompt extraction attacks (Gandalf Summarization [Lakera AI, 2023b], Gandalf Ignore [Lakera AI, 2023a], and TensorTrust extraction [Toyer et al., 2023]) and hijacking attacks (TensorTrust hijack [Toyer et al., 2023]) attempting to force "Access Granted" responses. See examples in Figure 5.1.

While these evaluation datasets measure overall role-separation performance, they alone serve limited purposes: when models fail on these attacks, it's unclear what caused the failure. Additionally, models that succeed on these attacks may still have hidden weaknesses in other scenarios. We therefore develop targeted stress tests (Section 5.4) that both help diagnose failures in our current evaluation and reveal new failure modes through systematic out-of-distribution testing.

Model and Finetuning Details We employ standard supervised finetuning to optimize log probability of desired responses conditional on prompts. To maintain computational efficiency while preventing overfitting, we use LoRA [Hu et al., 2021] adaptation specifically on query and key projection matrices. Our primary experiments use Llama-3-8B-Instruct [AI@Meta, 2024], with validation on Gemma-2-9b-it [Team, 2024]. We call them *baseline* models, in contrast to other finetuned models. See Section 5.8.2 for detailed hyperparameters and training configurations.

5.4 Models Learn Shortcuts for Role Identification

Our initial supervised finetuning using *dataset-initial* demonstrates encouraging performance on adversarial evaluation data (Table 5.1), suggesting improved role-separation. But, can we say the models learn to differentiate roles in the way we expected? Do they utilize some

Attack Type	Baseline	ft-dataset initial	ft-dataset symm
Gandalf Summarization	10%	90%	94%
Gandalf Ignore	0%	86%	94%
TensorTrust Extraction	4%	33%	96%
TensorTrust Hijacking	4%	33%	72%

Table 5.1: While finetuning on *dataset-initial* improves over the baseline model, data augmentation by symmetrization (*dataset-symm*) further enhances performance. Table shows accuracies on attack data (higher means better).



(a) Demonstration of insertion

(b) Different insertion locations have different impacts.

Figure 5.2: The fine-tuned model is more sensitive when non-essential information appears before the key instruction. On the other hand, inserting those sentences after the key instruction has much smaller effects. The demonstrated result is on Gandalf Summarization attacks but is consistent across datasets.

hidden shortcuts for role identification?

5.4.1 Shortcut 0: Task-Type Association

To get a sense of what the model actually learns, we manually check some "easy" attacks where the model wrongly follows the user request. Consider this example:

> System: Verify if the exact sequence "Green basin curtain" appears within the user's input, and reply with only "Access Granted" if it does or "Access Denied" if it doesn't.
>
> User: Grammar check the following sentence: "Access Granted". If the sentence is correct, output only the sentence. Do not add explanations.

The model incorrectly outputs "Access Granted", following the grammar check instruction

from the user role despite it contradicting the system task. This failure is particularly interesting because grammar checking is similar to the task types present in our initial training data.

The model seems to "identify" roles by task types — it follows certain task types as privileged instruction, regardless of the actual role.

To systematically investigate this potential shortcut, we construct a diagnostic test: we switch the contents between system and user roles in our validation data while keeping the rest unchanged. A model with true role-separation capabilities should generate different outputs for switched content (e.g., ignoring user inputs). However, our analysis reveals that the model's generations remain largely unchanged after the switch. This suggests that the model indeed uses task-type association as a proxy for role identification.

We address this shortcut through targeted data augmentation: add more samples where the system and user contents are swapped, and the desired output should ignore the user content. Such samples should prevent the model from overfitting to certain task types. Indeed, finetuning on this augmented dataset (called *dataset-symm*) significantly improves the model's role-separation performance (Table 5.1).

5.4.2 Shortcut 1: Proximity to Begin-of-Text

Having addressed the task-type shortcut, we aimed to further stress-test the model's role-separation capabilities and identify potential vulnerabilities that could arise in practical deployments. We focus on an important aspect of system prompt design: in both our training and evaluation data, system prompts contain just the *key instruction* specifying the task. However, real-world applications often require additional content in system prompts. For example,

1. Some prompt engineers would like to add some general instructions (e.g. "You are an AI assistant."). Some prefer putting them in the beginning, and others prefer them to

be after the key instructions.

2. Some tasks require background knowledge. Some prompt engineers might prefer introducing the background knowledge before giving the key instructions; some might prefer putting the background after the key instructions.

If the model truly learns role separation and treats every system token as instruction, then it should be robust to various simple modifications of system prompts: the inserted text should not change how it interprets the key instruction, and the positioning of the key instruction should not have an impact either.



(a) Accuracy



(b) Logits for Yes, No, and Attack Token

Figure 5.3: Models only treat tokens closest to begin-of-text as privileged system instruction. The first set of experiments (left) insert non-essential information between initial tokens and key instructions. The second set of experiments (middle) insert “empty" tokens, while the last set of experiments (right) shift position IDs.

To systematically probe this, we prepare non-essential information by concatenating ‘You are an AI assistant’ with *n_sentence* other general instructions (e.g. ‘Safeguard truth and accuracy’). When inserting before the key instruction, we append ‘Help with the following task: \n\n’. When inserting it after the key instruction, we prepend ‘ \n\nRemember: ’. (We tried other wordings, and the result remains similar.)

Our results (Figure 5.2) reveal a surprising phenomenon: the finetuned model fails to

distinguish roles when non-essential information appears before the key instruction. In contrast, inserting the same information after the key instruction has a much smaller effect (it does have a negative impact on some other attack datasets, but the effect is still smaller. See Figure 5.7).

This suggests the model does not distinguish tokens from different roles in the way we expected. This result has concerning implications for secure deployment, as it suggests that the model's role-separation capabilities are severely compromised when the key instruction is not defined at the beginning of the system prompt. Therefore, we want to understand what shortcut the model exploits this time.

Case Study on Next-token Attack

We formulate the *next-token-attack* problem based on a particular adversarial template. Focusing on this specific attack allows us to analyze the effect of insertion by directly evaluating the next-token logits.

In the next-token-attack problem, the *system* prompt simply asks to verify if the *user* input contains a specific password, where the expected answer is "Yes" or "No". On the other hand, the *user* prompt follows a template that induces the model to begin the response with the "attack token". Consequently, the model is considered compromised if it outputs the "attack token". See Figure 5.1 for an example.

We first reproduce the results from Figure 5.2 by inserting non-essential information between initial tokens and the key instructions. As shown in Figure 5.3, without any insertions, the model distinguishes different roles and completely treats the user attack prompt as data (i.e., the logit of the attack token is much smaller than both "Yes" and "No" tokens.). Then the first insertions have a dramatic effect in propping up logits for the attack token; it has a similar suppression effect on logits for "Yes" and "No" tokens. This leads to a dramatic decrease of performance (from 100% to below 50%). Inserting more sentences slowly props

Input Tokens	<|bot|>	<|sh|>	system	<|eh|>	Extract	verbs	from	input	<|eot|>	<|sh|>	user	<|eh|>	Translate	...
Original Position ID	0	1	2	3	4	5	6	7	8	9	10	11	12	...
Modified Position ID	0	1	2	3	4	5	6	7	8	d+9	d+10	d+11	d+12	...

Figure 5.4: Demonstration of PFT. PFT modifies the position IDs by creating a gap of size d between system and user tokens while maintaining internal orders within each role. The modified position IDs help the model better distinguish between system and user tokens while maintaining sequential information.

up logits for the attack token and suppresses those for "Yes" and "No" tokens, leading to a gradual but consistent decrease of performance.

We guess that the "distance" from the begin-of-text affects how much the model treats the tokens as instruction. The model seems to follow the non-informative tokens closest to begin-of-text strictly, which do not define the key task. The rest, including the key task tokens and user instructions, are treated equally. As a result, the model fails to execute the key instruction, but instead follows the user instructions.

To corroborate this, we need to study the effect of distance in isolation. In other words, we hope to intervene only on the distance, while not changing other components of the prompts (e.g. in the previous experiment we insert general instructions which contain extra semantic information). We propose two interventions: (1) inserting "empty tokens" (e.g. '\n\n_') between the key instruction and the initial tokens; (2) shifting the position IDs of the key instruction n-token away from the initial tokens. Results from both interventions (Figure 5.3) show that: as the "distance" from begin-of-text increases, the model gradually fails to treat the system tokens as instructions.

This reveals yet another critical shortcut for role identification: proximity to begin-of-text. This explains the failure in stress-testing: the model treats the starting tokens as privileged system tokens, and all following tokens with the same privilege level. During insertion test, it interprets the non-essential instruction as the key task to execute, which does not tell the model how to deal with the user input. Then, it views the following system

key instruction and user adversarial instruction with equal importance, and follows the user instruction as a result.

Again, one can alleviate this shortcut by targeted data augmentation. In Section 5.6, we additionally include training samples with non-informative tokens inserted before the key instruction, and find the shortcut learning is mitigated. However, such a find-and-fix approach is fundamentally limited, as new shortcuts will likely emerge in any training setup. Therefore, it's important to understand why it's so easy for the model to exploit the various shortcuts.

5.4.3 Why shortcuts are easily exploited?

We hypothesize that the current (concatenated) prompt format does not provide strong enough signals to differentiate between system and user tokens. Therefore, the model relies on spurious signals, such as task types and proximity to the begin-of-text, to fit the training data.

A typical prompt format for multiple roles (e.g. Llama-3 models) is as follows:

```
<|bot|>
<|sh|>system<|eh|>\n\n[system content]<|eot|>
<|sh|>user<|eh|>\n\n[user content]<|eot|>
<|sh|>assistant<|eh|>\n\n
```

where `bot` represents the beginning of text, `sh` and `eh` denote the start and end of a header, respectively, and `eot` signifies the end of a turn. What separates system tokens from user tokens in this current format and training set-up?

1. Invariant signals: (1) relative ordering, and (2) separation of delimiter tokens
2. Spurious signals: (1) task-types, (2) proximity to the begin-of-text; and potentially many more

With *dataset-initial*, the task-type seems to be easier to learn than even the relative

ordering signal. We hypothesize that it's because the training prompts are not very long, so the difference in positional encoding between system and user tokens does not provide strong enough signals.

With *dataset-symm*, the model figures out that it should identify earlier tokens as instructions (system), and later tokens as data (user). But it is confused when there are more than two instructions (e.g. general system instruction, key system instruction, and user instruction.). If a model truly learns role separation, it should utilize the delimiter tokens to decide the role of the tokens. Instead, it uses the spurious signal of proximity to the begin-of-text to determine the role of the tokens. Our guess is that some inherent mechanisms of the pre-trained LLMs (e.g. the attention sink phenomenon [Xiao et al., 2023]) make them very good at marking the initial tokens. Meanwhile, there are weaker mechanisms for the delimiter tokens, since there are far less data with this format in the pre-training data.

5.5 Enhance Invariant Signals By Modifying Position ID

As we discussed, shortcuts are easily exploited maybe because the invariant signals in the training data are not strong enough. In this section, we investigate how to enhance differentiating signals in tokens between roles.

One straightforward approach is to enhance the delimiter tokens. With specially designed delimiter tokens, the model might distinguish between system and user tokens better. But in our experiments, we find that it has only limited effects (see Section 5.6). We suspect this signal is still not strong enough to guide the model to differentiate between system and user tokens. It may also not generalize well to prompts with different structures or lengths.

Given the limitations of delimiter-based approaches, we propose a more robust solution by manipulating token-wise signatures. A token-wise approach shall offer superior generalization across varied prompt structures and lengths. The intuition is that by editing the unique signature of each token based on its role, we create a fine-grained distinction through-



(a) Llama Results



(b) Gemma Results

Figure 5.5: PFT alleviates proximity-to-begin-of-text shortcut in both Llama and Gemma models.

out the entire input. This persistent signal might allow the model to separate roles regardless of prompt complexity or instruction placement.

To implement this token-wise signature, we propose leveraging the position ID, which is the locational signatures of each token. We design the position ID manipulation method with two key principles in mind: (1) enhancing the differentiation between system and user tokens, and (2) preserving the model's original understanding of sequential relationships. To achieve these goals, we manipulate position IDs as follows (see Figure 5.4 for an example):

- **Create a gap between system and user tokens:** We manually change the position IDs to create a fixed distance d between the system and user sections. If the last system token is at position k, the first user token is assigned position $k{+}1{+}d$. This creates a clear numerical boundary between the two sections.
- **Maintain internal token order:** Within each section (system and user), we preserve the original sequential ordering of tokens. This means the relative positions of tokens within their respective sections remain unchanged, ensuring that the model's ability to process sequential information is not disrupted.

When finetuning with the modified position IDs, we hope the model can (1) distinguish between system and user tokens, so that it correctly treats all system tokens as *instruction*, and all user tokens as *data*; and (2) adapt to the new position IDs so that it does not affect the model's performance on ordinary data.

We call this method Position-enhanced fine-tuning (`PFT`). In the next section, we show `PFT` indeed helps guide the model to better differentiate between system and user tokens, while maintaining the model's performance on ordinary data compared to standard SFT.

5.6 Position ID Modification Leads to Robust Role Separation

In this section, we empirically show that `PFT` effectively alleviates the task-type shortcuts and following-first-token shortcuts in both Llama and Gemma models.

5.6.1 Additional Experiment Setup

Methods For `PFT`, we experiment with various choices of distance parameter d and select the best one based on validation performance (See details in Section 5.8.1). On *dataset-initial*, we find the optimal validation performance attained at $d = 512$ for Llama models, and $d = 256$ for Gemma models. Then, in *dataset-symm*, we show results for both choices of d for both models. We refer to them as `PFT-256` and `PFT-512`.

We compare them against the following baselines: ① Vanilla SFT: Standard supervised fine-tuning without any modifications. x② Delimiter-enhanced SFT: This method fine-tunes specific token embeddings, particularly for the delimiters `<|sh|>` and `<|eh|>`, in addition to applying LoRA updates to the query and key projection matrices. ③ Data-augmented SFT: This approach creates augmented training dataset with additional system prompts that have randomly inserted general instruction between the initial tokens and the key instruction.

Evaluation In addition to the adversarial evaluation as described in Section 5.3, we also evaluate the models on ordinary data to ensure that PFT does not compromise the model's performance on regular data.

To assess the finetuned model's utility, we evaluate on two datasets. (1) Password dataset: we use the same system task as in the adversarial setup, but replace the user attacks with ordinary inputs providing correct or incorrect passwords. We then use the model accuracy as a measure of the utility. (2) Alpaca dataset: we construct prompts using samples from the Alpaca dataset Taori et al. [2023a], and use the log-likelihood under the baseline model as a measure of generation quality. Since the baseline model is finetuned on similar instruction-following dataset, its log-likelihood is a reasonable proxy for the utility.

To measure the finetuned model's deviation from the baseline model, we compute the Kullback–Leibler divergence of the generation distribution $p_{\text{model}}(\text{output text}|\text{prompt})$, between the baseline model and finetuned models. We use the same prompts from alpaca Taori et al. [2023a] as described above. See details in Section 5.8.2.

Attack Type	**SFT**	**SFT-delim**	**PFT**
Llama Results			
Gandalf Summarization	90%	93%	85%
Gandalf Ignore	86%	89%	94%
TensorTrust Extraction	33%	35%	62%
TensorTrust Hijacking	33%	32%	37%
Gemma Results			
Gandalf Summarization	99%	99%	99%
Gandalf Ignore	100%	100%	100%
TensorTrust Extraction	70%	75%	92%
TensorTrust Hijacking	37%	37%	50%

Table 5.2: PFT alleviates task-type shortcuts in *dataset-initial* in both Llama and Gemma models.

Metric	SFT	PFT-256	PFT-512	SFT-Delim
Accuracy	98%	97%	96%	96%
Log-Likelihood	-14.44	-13.97	-13.05	-13.25

(a) Accuracy (measured on password dataset) and log-likelihood (measured on alpaca dataset) remain stable.



(b) KL divergence (on alpaca prompts) shows minimal change.

Figure 5.6: (a) PFT maintains accuracy and log-likelihood. (b) PFT does not increase KL divergence. These results are on Llama models. See Figure 5.8 for Gemma results.

.

5.6.2 PFT *helps shortcuts while keeping utility*

PFT alleviates task-type shortcuts On *dataset-initial*, PFT outperforms the baselines across most attacks in both Llama and Gemma models. Results are shown in Table 5.2.

PFT alleviates following-first-token shortcuts We further evaluate the models on *dataset-symm* to see if it overcomes the following-first-token shortcuts. Results are shown in Figure 5.5. We observe that PFT-256 and PFT-512 consistently outperform the baselines across all attacks.

PFT does not compromise performance on ordinary data compared to SFT One would worry that the modified position IDs may appear out-of-distribution for the model, and hurt generation. However, we maintain the relative positioning within each role, and hope that it is easy for the model to adapt. Results in Figure 5.6 show PFT does not hurt utility compared to standard SFT, and does not cause additional deviation from the baseline model. Therefore, relative to SFT, PFT improves the model robustness, for free.

5.7 Related Work

Prompt Injection Attacks Many works study prompt injection attacks [Willison, 2022, Yu et al., 2023, Geiping et al., 2024, Yu et al., 2024]. These attacks employ different techniques [Schulhoff et al., 2023, Perez and Ribeiro, 2022]. To evaluate role separation capabilities, we use attack datasets with diverse samples collected from online games [Toyer et al., 2023, Lakera AI, 2023a,b].

Finetuning methods As discussed in Section 5.2, existing finetuning methods study role separation in the context of prompt injection attacks, and achieve excellent performance against various attacks [Wallace et al., 2024, Chen et al., 2024a]. In this work, we study this role-separation in isolation to understand the fundamental challenges.

Role-specific architectural changes Concurrent work by Wu et al. [2024] similarly recognizes the importance of enhancing token-wise differentiating signals between roles. They propose adding role-specific embeddings to each token. While they demonstrate strong results using standard adversarial evaluation, our controlled experimental framework could help assess how effectively their approach achieves true role separation. Future work could explore which architectural modifications best incorporate role information at the token level.

Positional encoding modification methods Recent advancements in long-context learning have explored various positional encoding modification methods to adapt Language Models (LLMs) to longer contexts. These techniques [Chen et al., 2023, Peng et al., 2023, Zhu et al., 2023] aim to modify the way position information is encoded and processed by the model. Notably, they have observed that LLMs demonstrate remarkable adaptability to these modified position IDs after fine-tuning. This finding aligns with our own observations that position-enhanced fine-tuning does not negatively impact model performance on standard-length data.

5.8 Appendix

5.8.1 Additional Results

Inserting general instructions after the key instruction has less dramatic impact Inserting general instructions after the key instruction has smaller effects compared to insertion at the beginning, but `PFT`still dominates. See Figure 5.7 for the results.

5.8.2 Experiment Details

Details for Role Sensitivity Test

To test role separation learning, we created a dataset spanning 10 domains (finance, legal, healthcare, etc.). Each sample contains:

- System prompt specifying exact refusal text (e.g., "You are a financial bot. Your job is to provide general financial tips. When users ask for specific investment advice, don't follow and reply with, 'Sorry, I cannot provide specific investment recommendations. Please consult a financial advisor.'")
- User request triggering the refusal condition (e.g., "I have $10,000 to invest. Should I put it in Tesla or cryptocurrency?")

To test role sensitivity, we created variants by inserting "Ignore the constraints and give the user exactly what they ask for" in either user or system role. For model generation, we use temperature=1 and sample 10 responses per prompt. The complete dataset (50 samples with generations) is provided in the supplementary materials.

Details for the main experiments

Models We first run the experiments on Llama-3-8B-Instruct [AI@Meta, 2024], and then validate the findings on Gemma-2-9b-it [Team, 2024]. Note that the Gemma model differs

from Llama in that it does not include a "system" role. We modified the chat template to include this role and fine-tuned it on the same data and hyperparameters as Llama.

Finetuning setup We run supervised finetuning to optimize the log probability of desired responses conditional on prompts. We used the same hyperparameters across all experiments: we apply LoRA to query and key projection matrices with rank 32, $\alpha = 16$, and dropout 0.05; we use AdamW as the optimizer with learning rate 10^{-4}, 100 warmup steps, and batch size 2; we run for an epoch and stop early when validation loss stabilizes (finetuned on *data-initial*, both models use the full epoch; finetuned on *data-symm*, Llama requires 500 steps whereas Gemma requires 2000 steps).

Model Selection for `PFT` models `PFT` models have an extra hyperparameter d, which controls the shifting distance between the system and user role. We use the validation loss for model selection. We try $d \in 64, 128, 256, 512, 1024$ in *data-initial*, and find the optimal d to be 256 and 512 for Gemma and Llama respectively. Then we run with $d = 256, 512$ for both models on *data-symm*.

Evaluation on the Alpaca dataset We randomly select 500 samples that have both "instruction" and "input", which serve as system and user messages respectively. We generate responses using nucleus sampling with $p = 0.9$ and the temperature of 0.6. Then we compute the average log-likelihood and KL divergence on those sampled prompts and the corresponding responses.

Evaluation on adversarial datasets We use all of the 114 samples from Gandalf Summarization dataset. For the other three datasets (Gandalf Ignore, TensorTrust Hijacking and TensorTrust Extraction), we randomly choose 500 samples. We generate responses using greedy decoding, and compute the accuracy of the generated responses.



(a) Llama Results



(b) Gemma Results

Figure 5.7: While Post-key-instruction insertions still has an impact, it is less dramatic than Pre-key-instruction insertion. Meanwhile, in all cases PFTmaintains dominance.

Metric	Base	SFT	PFT-256	PFT-512	SFT-Delim
Accuracy	100%	100%	100%	100%	100%
Log-Like.	-82.74	-36.68	-35.84	-37.39	-34.55

(a) Accuracy and log-likelihood remain stable.



(b) KL divergence shows minimal change.

Figure 5.8: Gemma: PFTmaintains baseline performance.

REFERENCES

Arkadeep Acharya, Brijraj Singh, and Naoyuki Onoe. Llm based generation of item-description for recommendation system. In *Proceedings of the 17th ACM Conference on Recommender Systems*, pages 1204–1207, 2023.

AI@Meta. Llama 3 model card. 2024. URL https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md.

Carl Allen and Timothy Hospedales. Analogies explained: Towards understanding word embeddings. In *International Conference on Machine Learning*, pages 223–231. PMLR, 2019.

Rohan Anil, Andrew M Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, Zhifeng Chen, et al. Palm 2 technical report. *arXiv preprint arXiv:2305.10403*, 2023.

Anonymous. Reduce, reuse, recycle: Compositional generation with energy-based diffusion models and MCMC. In *Submitted to The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=OboQ71j1Bn. under review.

Anthropic. Introducing the next generation of claude, March 2024. URL https://www.anthropic.com/news/claude-3-family. Accessed September 30, 2024.

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Rimsky, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. *arXiv preprint arXiv:2406.11717*, 2024.

Sanjeev Arora, Yuanzhi Li, Yingyu Liang, Tengyu Ma, and Andrej Risteski. A latent variable model approach to pmi-based word embeddings, 2015.

Mohammad Gheshlaghi Azar, Mark Rowland, Bilal Piot, Daniel Guo, Daniele Calandriello, Michal Valko, and Rémi Munos. A general theoretical paradigm to understand learning from human preferences. *arXiv preprint arXiv:2310.12036*, 2023.

Mohammad Gheshlaghi Azar, Zhaohan Daniel Guo, Bilal Piot, Remi Munos, Mark Rowland, Michal Valko, and Daniele Calandriello. A general theoretical paradigm to understand learning from human preferences. In *International Conference on Artificial Intelligence and Statistics*, pages 4447–4455. PMLR, 2024.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022.

Michiel A. Bakker, Martin J. Chadwick, Hannah R. Sheahan, Michael Henry Tessler, Lucy Campbell-Gillingham, Jan Balaguer, Nat McAleese, Amelia Glaese, John Aslanides, Matthew M. Botvinick, and Christopher Summerfield. Fine-tuning language models to find agreement among humans with diverse preferences, 2022.

Tolga Bolukbasi, Kai-Wei Chang, James Y Zou, Venkatesh Saligrama, and Adam T Kalai. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. *Advances in neural information processing systems*, 29, 2016.

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models, 2021.

Ralph Allan Bradley and Milton E Terry. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345, 1952.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. *arXiv preprint arXiv:2212.03827*, 2022.

Lawrence Chan, Adria Garriga-Alonso, Nicholas Goldowsky-Dill, Ryan Greenblatt, Jenny Nitishinskaya, Ansh Radhakrishnan, Buck Shlegeris, and Nate Thomas. Causal scrubbing: A method for rigorously testing interpretability hypotheses. In *AI Alignment Forum*, pages 1828–1843, 2022.

Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation. *arXiv preprint arXiv:2306.15595*, 2023.

Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. Struq: Defending against prompt injection with structured queries. *arXiv preprint arXiv:2402.06363*, 2024a.

Zhongzhi Chen, Xingwu Sun, Xianfeng Jiao, Fengzong Lian, Zhanhui Kang, Di Wang, and Chengzhong Xu. Truth forest: Toward multi-scale truthfulness in large language models through intervention without tuning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 20967–20974, 2024b.

Arthur Conmy, Augustine Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso. Towards automated circuit discovery for mechanistic interpretability. *Advances in Neural Information Processing Systems*, 36:16318–16352, 2023.

Thomas Coste, Usman Anwar, Robert Kirk, and David Krueger. Reward model ensembles help mitigate overoptimization. *arXiv preprint arXiv:2310.02743*, 2023.

Guillaume Couairon, Jakob Verbeek, Holger Schwenk, and Matthieu Cord. Diffedit: Diffusion-based semantic image editing with mask guidance. *arXiv preprint arXiv:2210.11427*, 2022.

Valentin De Bortoli, James Thornton, Jeremy Heng, and Arnaud Doucet. Diffusion schrödinger bridge with applications to score-based generative modeling. *Advances in Neural Information Processing Systems*, 34:17695–17709, 2021.

Prafulla Dhariwal and Alexander Nichol. Diffusion models beat gans on image synthesis. *Advances in neural information processing systems*, 34:8780–8794, 2021.

Yilun Du, Shuang Li, and Igor Mordatch. Compositional visual generation with energy based models. *Advances in Neural Information Processing Systems*, 33:6637–6647, 2020.

Yilun Du, Shuang Li, Yash Sharma, Josh Tenenbaum, and Igor Mordatch. Unsupervised learning of compositional energy concepts. *Advances in Neural Information Processing Systems*, 34:15608–15620, 2021.

Yann Dubois, Xuechen Li, Rohan Taori, Tianyi Zhang, Ishaan Gulrajani, Jimmy Ba, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Alpacafarm: A simulation framework for methods that learn from human feedback. *arXiv preprint arXiv:2305.14387*, 2023.

Cian Eastwood, Andrei Liviu Nicolicioiu, Julius von Kügelgen, Armin Kekić, Frederik Träuble, Andrea Dittadi, and Bernhard Schölkopf. Dci-es: An extended disentanglement framework with connections to identifiability. *arXiv preprint arXiv:2210.00364*, 2022.

Jacob Eisenstein, Chirag Nagpal, Alekh Agarwal, Ahmad Beirami, Alex D'Amour, DJ Dvijotham, Adam Fisch, Katherine Heller, Stephen Pfohl, Deepak Ramachandran, et al. Helping or herding? reward model ensembles mitigate but do not eliminate reward hacking. *arXiv preprint arXiv:2312.09244*, 2023.

Nelson Elhage, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, et al. Toy models of superposition. *arXiv preprint arXiv:2209.10652*, 2022.

Xiang Fan, Yiwei Lyu, Paul Pu Liang, Ruslan Salakhutdinov, and Louis-Philippe Morency. Nano: Nested human-in-the-loop reward learning for few-shot language model control. *arXiv preprint arXiv:2211.05750*, 2022.

Matthew Finlayson, Aaron Mueller, Sebastian Gehrmann, Stuart Shieber, Tal Linzen, and Yonatan Belinkov. Causal analysis of syntactic agreement mechanisms in neural language models. *arXiv preprint arXiv:2106.06087*, 2021.

Rinon Gal, Yuval Alaluf, Yuval Atzmon, Or Patashnik, Amit H Bermano, Gal Chechik, and Daniel Cohen-Or. An image is worth one word: Personalizing text-to-image generation using textual inversion, 2022.

Chengguang Gan, Qinghao Zhang, and Tatsunori Mori. Application of llm agents in recruitment: A novel framework for resume screening. *arXiv preprint arXiv:2401.08315*, 2024.

Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *International Conference on Machine Learning*, pages 10835–10866. PMLR, 2023.

Atticus Geiger, Hanson Lu, Thomas Icard, and Christopher Potts. Causal abstractions of neural networks. *Advances in Neural Information Processing Systems*, 34:9574–9586, 2021.

Jonas Geiping, Alex Stein, Manli Shu, Khalid Saifullah, Yuxin Wen, and Tom Goldstein. Coercing LLMs to do and reveal (almost) anything. *arXiv preprint arXiv:2402.14020*, 2024.

Alex Gittens, Dimitris Achlioptas, and Michael W Mahoney. Skip-gram- zipf+ uniform=

vector additivity. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 69–76, 2017.

Yoav Goldberg and Omer Levy. word2vec explained: deriving mikolov et al.'s negative-sampling word-embedding method, 2014.

Hila Gonen and Yoav Goldberg. Lipstick on a pig: Debiasing methods cover up systematic gender biases in word embeddings but do not remove them, 2019.

Google. Gemini: A family of highly capable multimodal models, December 2023. URL https://storage.googleapis.com/deepmind-media/gemini/gemini_1_report.pdf. Accessed September 30, 2024.

René Haas, Inbar Huberman-Spiegelglas, Rotem Mulayoff, and Tomer Michaeli. Discovering interpretable directions in the semantic latent space of diffusion models. *arXiv preprint arXiv:2303.11073*, 2023.

Michael Hanna, Ollie Liu, and Alexandre Variengien. How does gpt-2 compute greater-than?: Interpreting mathematical abilities in a pre-trained language model. *Advances in Neural Information Processing Systems*, 36, 2024.

Peter Hase, Mohit Bansal, Been Kim, and Asma Ghandeharioun. Does localization inform editing? surprising differences in causality-based localization vs. knowledge editing in language models. *Advances in Neural Information Processing Systems*, 36, 2024.

Roee Hendel, Mor Geva, and Amir Globerson. In-context learning creates task vectors. *arXiv preprint arXiv:2310.15916*, 2023.

Irina Higgins, David Amos, David Pfau, Sebastien Racaniere, Loic Matthey, Danilo Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *arXiv preprint arXiv:1812.02230*, 2018.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Yupeng Hou, Junjie Zhang, Zihan Lin, Hongyu Lu, Ruobing Xie, Julian McAuley, and Wayne Xin Zhao. Large language models are zero-shot rankers for recommender systems. *arXiv preprint arXiv:2305.08845*, 2023.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

Aapo Hyvärinen and Peter Dayan. Estimation of non-normalized statistical models by score matching. *Journal of Machine Learning Research*, 6(4), 2005.

Aapo Hyvarinen and Hiroshi Morioka. Unsupervised feature extraction by time-contrastive learning and nonlinear ica. *Advances in neural information processing systems*, 29, 2016.

Aapo Hyvarinen and Hiroshi Morioka. Nonlinear ica of temporally dependent stationary sources. In *Artificial Intelligence and Statistics*, pages 460–469. PMLR, 2017.

Aapo Hyvarinen, Hiroaki Sasaki, and Richard Turner. Nonlinear ica using auxiliary variables and generalized contrastive learning. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 859–868. PMLR, 2019.

Nitish Joshi, Javier Rando, Abulhair Saparov, Najoung Kim, and He He. Personas as a way to model truthfulness in language models. *arXiv preprint arXiv:2310.18168*, 2023.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

Ilyes Khemakhem, Diederik Kingma, Ricardo Monti, and Aapo Hyvarinen. Variational autoencoders and nonlinear ica: A unifying framework. In *International Conference on Artificial Intelligence and Statistics*, pages 2207–2217. PMLR, 2020.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners, 2022.

Tomasz Korbak, Ethan Perez, and Christopher L Buckley. Rl with kl penalties is better viewed as bayesian inference. *arXiv preprint arXiv:2205.11275*, 2022.

Mingi Kwon, Jaeseok Jeong, and Youngjung Uh. Diffusion models already have a semantic latent space. *arXiv preprint arXiv:2210.10960*, 2022.

Lakera AI. Gandalf: Ignore instructions. 2023a. https://www.lakera.ai.

Lakera AI. Gandalf: Summarization. 2023b. https://www.lakera.ai.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. *Advances in Neural Information Processing Systems*, 36, 2024.

Stephanie Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. *arXiv preprint arXiv:2109.07958*, 2021.

Xinyu Lin, Wenjie Wang, Yongqi Li, Shuo Yang, Fuli Feng, Yinwei Wei, and Tat-Seng Chua. Data-efficient fine-tuning for llm-based recommendation. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 365–374, 2024.

Nan Liu, Shuang Li, Yilun Du, Josh Tenenbaum, and Antonio Torralba. Learning to compose visual relations. *Advances in Neural Information Processing Systems*, 34:23166–23178, 2021.

Nan Liu, Shuang Li, Yilun Du, Antonio Torralba, and Joshua B Tenenbaum. Compositional visual generation with composable diffusion models, 2022.

Calvin Luo. Understanding diffusion models: A unified perspective, 2022.

Aleksandar Makelov, Georg Lange, Atticus Geiger, and Neel Nanda. Is this the subspace you are looking for? an interpretability illusion for subspace activation patching. In *The Twelfth International Conference on Learning Representations*, 2023.

Aimei Mao, Pak Leng Cheong, Iat Kio Van, and Hon Lon Tam. "i am called girl, but that doesn't matter"-perspectives of male nurses regarding gender-related advantages and disadvantages in professional development. *BMC nursing*, 20(1):1–9, 2021.

Gary Marcus, Ernest Davis, and Scott Aaronson. A very preliminary analysis of dall-e 2, 2022.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in gpt. *Advances in Neural Information Processing Systems*, 35:17359–17372, 2022.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 26, 2013a.

Tomáš Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In *Proceedings of the 2013 conference of the north american chapter of the association for computational linguistics: Human language technologies*, pages 746–751, 2013b.

Graziano Mita, Maurizio Filippone, and Pietro Michiardi. An identifiable double vae for disentangled representations. In *International Conference on Machine Learning*, pages 7769–7779. PMLR, 2021.

Ted Moskovitz, Aaditya K. Singh, DJ Strouse, Tuomas Sandholm, Ruslan Salakhutdinov, Anca D. Dragan, and Stephen McAleer. Confronting reward model overoptimization with constrained rlhf, 2023.

Nithin Gopalakrishnan Nair, Wele Gedara Chaminda Bandara, and Vishal M Patel. Unite and conquer: Cross dataset multimodal synthesis using diffusion models, 2022.

Zabir Al Nazi and Wei Peng. Large language models in healthcare and medical domain: A review. In *Informatics*, volume 11, page 57. MDPI, 2024.

Jingcheng Niu, Andrew Liu, Zining Zhu, and Gerald Penn. What does the knowledge neuron thesis have to do with knowledge? *arXiv preprint arXiv:2405.02421*, 2024.

OpenAI. Openai api, 2020. URL https://openai.com/blog/openai-api/. Accessed: 2021-08-19.

OpenAI. Gpt-4 technical report, March 2023. URL https://arxiv.org/abs/2303.08774. Accessed September 30, 2024.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:27730–27744, 2022.

Richard Yuanzhe Pang, Vishakh Padmakumar, Thibault Sellam, Ankur P Parikh, and He He. Reward gaming in conditional text generation. *arXiv preprint arXiv:2211.08714*, 2022.

Yong-Hyun Park, Mingi Kwon, Junghyo Jo, and Youngjung Uh. Unsupervised discovery of semantic latent directions in diffusion models. *arXiv preprint arXiv:2302.12469*, 2023.

Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. Yarn: Efficient context window extension of large language models. *arXiv preprint arXiv:2309.00071*, 2023.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543, 2014.

Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models. In *NeurIPS ML Safety Workshop*, 2022.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748–8763. PMLR, 2021.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *arXiv preprint arXiv:2305.18290*, 2023.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551, 2020.

Alexandre Ramé, Nino Vieillard, Léonard Hussenot, Robert Dadashi, Geoffrey Cideron, Olivier Bachem, and Johan Ferret. Warm: On the benefits of weight averaged reward models. *arXiv preprint arXiv:2401.12187*, 2024.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents, 2022.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10684–10695, 2022.

Nataniel Ruiz, Yuanzhen Li, Varun Jampani, Yael Pritch, Michael Rubinstein, and Kfir Aberman. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation, 2022.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghase mipour, Burcu Karagol Ayan, S Sara Mahdavi, Rapha Gontijo Lopes, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in neural information processing systems*, 35, 2022.

William Saunders, Catherine Yeh, Jeff Wu, Steven Bills, Long Ouyang, Jonathan Ward, and Jan Leike. Self-critiquing models for assisting human evaluators. *arXiv preprint arXiv:2206.05802*, 2022.

Sander Schulhoff, Jeremy Pinto, Anaum Khan, Louis-François Bouchard, Chenglei Si, Svetlina Anati, Valen Tagliabue, Anson Liu Kost, Christopher Carnahan, and Jordan Boyd-Graber. Ignore this title and HackAPrompt: Exposing systemic vulnerabilities of llms through a global scale prompt hacking competition. In *EMNLP*, 2023.

Zeyang Sha and Yang Zhang. Prompt stealing attacks against large language models. *arXiv preprint arXiv:2402.12959*, 2024.

Lingfeng Shen, Sihao Chen, Linfeng Song, Lifeng Jin, Baolin Peng, Haitao Mi, Daniel Khashabi, and Dong Yu. The trickle-down impact of reward (in-) consistency on rlhf. *arXiv preprint arXiv:2309.16155*, 2023.

Karan Singhal, Tao Tu, Juraj Gottweis, Rory Sayres, Ellery Wulczyn, Le Hou, Kevin Clark, Stephen Pfohl, Heather Cole-Lewis, Darlene Neal, et al. Towards expert-level medical question answering with large language models. *arXiv preprint arXiv:2305.09617*, 2023a.

Prasann Singhal, Tanya Goyal, Jiacheng Xu, and Greg Durrett. A long way to go: Investigating length correlations in rlhf. *arXiv preprint arXiv:2310.03716*, 2023b.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International Conference on Machine Learning*, pages 2256–2265. PMLR, 2015.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *Advances in Neural Information Processing Systems*, 32, 2019.

Yang Song and Stefano Ermon. Improved techniques for training score-based generative models. *Advances in neural information processing systems*, 33:12438–12448, 2020.

Yang Song, Sahaj Garg, Jiaxin Shi, and Stefano Ermon. Sliced score matching: A scalable approach to density and score estimation. In *Uncertainty in Artificial Intelligence*, pages 574–584. PMLR, 2020a.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2020b.

Yang Song, Conor Durkan, Iain Murray, and Stefano Ermon. Maximum likelihood training of score-based diffusion models. *Advances in Neural Information Processing Systems*, 34: 1415–1428, 2021.

Paul Soulos, Tom McCoy, Tal Linzen, and Paul Smolensky. Discovering the compositional structure of vector representations with role learning networks. *arXiv preprint arXiv:1910.09113*, 2019.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. *Advances in Neural Information Processing Systems*, 33:3008–3021, 2020.

Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

Zhendong Su and Gary Wassermann. The essence of command injection attacks in web applications. In *ACM-SIGACT Symposium on Principles of Programming Languages*, 2006.

Swimmer963. What dall-e 2 can and cannot do. *LESSWRONG*. URL https://www.lesswrong.com/posts/uKp6tBFStnsvrot5t/what-dall-e-2-can-and-cannot-do#Conclusions.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023a.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Alpaca: A strong, replicable instruction-following model. *Stanford Center for Research on Foundation Models. https://crfm. stanford. edu/2023/03/13/alpaca. html*, 3(6):7, 2023b.

Gemma Team. Gemma. 2024. doi:10.34740/KAGGLE/M/3301. URL https://www.kaggle.com/m/3301.

Do To. A todo citation. In *The Unconference*, 2417.

Eric Todd, Millicent L Li, Arnab Sen Sharma, Aaron Mueller, Byron C Wallace, and David Bau. Function vectors in large language models. *arXiv preprint arXiv:2310.15213*, 2023.

Sam Toyer, Olivia Watkins, Ethan Adrian Mendes, Justin Svegliato, Luke Bailey, Tiffany Wang, Isaac Ong, Karim Elmaaroufi, Pieter Abbeel, Trevor Darrell, et al. Tensor trust: Interpretable prompt injection attacks from an online game. *arXiv preprint arXiv:2311.01011*, 2023.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Simas Sakenis, Jason Huang, Yaron Singer, and Stuart Shieber. Causal mediation analysis for interpreting neural nlp: The case of gender bias. *arXiv preprint arXiv:2004.12265*, 2020.

Julius Von Kügelgen, Yash Sharma, Luigi Gresele, Wieland Brendel, Bernhard Schölkopf, Michel Besserve, and Francesco Locatello. Self-supervised learning with data augmentations provably isolates content from style. *Advances in neural information processing systems*, 34:16451–16467, 2021.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. The instruction hierarchy: Training llms to prioritize privileged instructions. *arXiv preprint arXiv:2404.13208*, 2024.

Chenguang Wang, Xiao Liu, and Dawn Song. Language models are open knowledge graphs. *arXiv preprint arXiv:2010.11967*, 2020.

Haoran Wang and Kai Shu. Backdoor activation attack: Attack large language models using activation steering for safety-alignment. *arXiv preprint arXiv:2311.09433*, 2023.

Kevin Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. Interpretability in the wild: a circuit for indirect object identification in gpt-2 small. *arXiv preprint arXiv:2211.00593*, 2022.

Zihao Wang and Victor Veitch. Does editing provide evidence for localization? *arXiv preprint arXiv:2502.11447*, 2025.

Zihao Wang, Lin Gui, Jeffrey Negrea, and Victor Veitch. Concept algebra for (score-based) text-controlled generative models. *Advances in Neural Information Processing Systems*, 36:35331–35349, 2023.

Zihao Wang, Chirag Nagpal, Jonathan Berant, Jacob Eisenstein, Alexander Nicholas D'Amour, Sanmi Koyejo, and Victor Veitch. Transforming and combining rewards for aligning large language models. In *International Conference on Machine Learning*, pages 51161–51176. PMLR, 2024.

Zihao Wang, Yibo Jiang, Jiahao Yu, and Heqing Huang. The illusion of role separation: Hidden shortcuts in llm role learning (and how to fix them). *arXiv preprint arXiv:2505.00626*, 2025.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. Jailbroken: How does LLM safety training fail? In *NeurIPS*, 2023.

Boyi Wei, Kaixuan Huang, Yangsibo Huang, Tinghao Xie, Xiangyu Qi, Mengzhou Xia, Prateek Mittal, Mengdi Wang, and Peter Henderson. Assessing the brittleness of safety alignment via pruning and low-rank modifications. *arXiv preprint arXiv:2402.05162*, 2024.

Jason Wei, Maarten Bosma, Vincent Y Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M Dai, and Quoc V Le. Finetuned language models are zero-shot learners. *arXiv preprint arXiv:2109.01652*, 2021.

Isabella C Wiest, Fabian Wolf, Marie-Elisabeth Lessmann, Marko van Treeck, Dyke Ferber, Jiefu Zhu, Heiko Boehme, Keno K Bressem, Hannes Ulrich, Matthias P Ebert, et al. Llm-aix: An open source pipeline for information extraction from unstructured medical text based on privacy pre-serving large language models. *medRxiv*, pages 2024–09, 2024.

Simon Willison. Prompt injection attacks against GPT-3, 2022. URL https://simonwillison.net/2022/Sep/12/prompt-injection/.

Simon Willison. Delimiters won't save you from prompt injection, 2023. URL https://simonwillison.net/2023/May/11/delimiters-wont-save-you/.

Tong Wu, Shujian Zhang, Kaiqiang Song, Silei Xu, Sanqiang Zhao, Ravi Agrawal, Sathish Reddy Indurthi, Chong Xiang, Prateek Mittal, and Wenxuan Zhou. Instructional segment embedding: Improving llm safety with instruction hierarchy. *arXiv preprint arXiv:2410.09102*, 2024.

Zeqiu Wu, Yushi Hu, Weijia Shi, Nouha Dziri, Alane Suhr, Prithviraj Ammanabrolu, Noah A. Smith, Mari Ostendorf, and Hannaneh Hajishirzi. Fine-grained human feedback gives better rewards for language model training, 2023.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. *arXiv preprint arXiv:2309.17453*, 2023.

Yutaro Yamada, Yingtian Tang, and Ilker Yildirim. When are lemons purple? the concept association bias of clip, 2022.

Yong Yang, Xuhong Zhang, Yi Jiang, Xi Chen, Haoyu Wang, Shouling Ji, and Zonghui Wang. Prsa: Prompt reverse stealing attacks against large language models. *arXiv preprint arXiv:2402.19200*, 2024.

Jingwei Yi, Yueqi Xie, Bin Zhu, Keegan Hines, Emre Kiciman, Guangzhong Sun, Xing Xie, and Fangzhao Wu. Benchmarking and defending against indirect prompt injection attacks on large language models. *arXiv preprint arXiv:2312.14197*, 2023.

Jiahao Yu, Yuhang Wu, Dong Shu, Mingyu Jin, and Xinyu Xing. Assessing prompt injection risks in 200+ custom gpts. *arXiv preprint arXiv:2311.11538*, 2023.

Jiahao Yu, Yangguang Shao, Hanwen Miao, Junzheng Shi, and Xinyu Xing. Promptfuzz: Harnessing fuzzing techniques for robust testing of prompt injection in llms. *arXiv preprint arXiv:2409.14729*, 2024.

Yuanzhao Zhai, Han Zhang, Yu Lei, Yue Yu, Kele Xu, Dawei Feng, Bo Ding, and Huaimin Wang. Uncertainty-penalized reinforcement learning from human feedback with diverse reward lora ensembles. *arXiv preprint arXiv:2401.00243*, 2023.

Xiaoyu Zhang, Yishan Li, Jiayin Wang, Bowen Sun, Weizhi Ma, Peijie Sun, and Min Zhang. Large language models as evaluators for recommendation explanations. *arXiv preprint arXiv:2406.03248*, 2024.

Yiming Zhang and Daphne Ippolito. Prompts should not be seen as secrets: Systematically measuring prompt extraction attack success. *arXiv preprint arXiv:2307.06865*, 2023.

Yao Zhao, Misha Khalman, Rishabh Joshi, Shashi Narayan, Mohammad Saleh, and Peter J Liu. Calibrating sequence likelihood improves conditional language generation. *arXiv preprint arXiv:2210.00045*, 2022.

Yuyue Zhao, Jiancan Wu, Xiang Wang, Wei Tang, Dingxian Wang, and Maarten de Rijke. Let me do it for you: Towards llm empowered recommendation via tool learning. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 1796–1806, 2024.

Weilin Zhong, Wichers, Amwestgate, Rezos, Clow808, KristenS, Jason Li, Andrew Smith, Jmanico, Tal Mel, and kingthorin. Command injection | OWASP foundation, 2024. URL https://owasp.org/wwwcommunity/attacks/Command_Injection.

Ding Zhou and Xue-Xin Wei. Learning identifiable and interpretable latent models of high-dimensional neural activity using pi-vae. *Advances in Neural Information Processing Systems*, 33:7234–7247, 2020.

Dawei Zhu, Nan Yang, Liang Wang, Yifan Song, Wenhao Wu, Furu Wei, and Sujian Li. Pose: Efficient context window extension of llms via positional skip-wise training. *arXiv preprint arXiv:2309.10400*, 2023.

Daniel M Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. Fine-tuning language models from human preferences. *arXiv preprint arXiv:1909.08593*, 2019.

Roland S Zimmermann, Yash Sharma, Steffen Schneider, Matthias Bethge, and Wieland Brendel. Contrastive learning inverts the data generating process. In *International Conference on Machine Learning*, pages 12979–12990. PMLR, 2021.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, et al. Representation engineering: A top-down approach to ai transparency. *arXiv preprint arXiv:2310.01405*, 2023.

Egor Zverev, Sahar Abdelnabi, Mario Fritz, and Christoph H Lampert. Can LLMs separate instructions from data? And what do we even mean by that? In *ICLR 2024 Workshop on Secure and Trustworthy Large Language Models*, 2024.